
PHILIPS Lighting



Core & Coil (71A) MH ~LT~ 175W

CORE & COIL HID 71A5191001D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	M110
Lamp Type	50W MH
Number Of Lamps	1 piece/unit
Circuit Type	HX-HPF
Ballast Type	Magnetic HID
Base Model	71A5191
Core Size	3 X 4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI533-H4
Ignitor Temperature Rating	105°C
Capacitor Value	6 MFD
Capacitor Catalog Number	7C060L30RA
Capacitor Requirements	280V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.25 in
Capacitor Height	2.75 in
Automatic Restart	No


Dperating and Electrical nput Voltage	120/208/240/277 V
	120/208/240/277 V
nput Frequency	60 Hz
nput Current (Open Circuit)	1.2/0.68/0.59/0.51 A
nput Current (Starting)	0.46/0.27/0.17/0.2 A
nput Current (Short Circuit)	0.42-0.65/0.25-0.37/0.21-0.32/0.16-0.27 A
Secondary Short Circuit Current	0.7-0.88 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	254 V
nput Current (Nom)	0.58/0.33/0.29/0.25 A A
nput Power (Nom)	67 W
Rated Lamp Power	50 W
Niring	
Wire Striplength	0.5 mm
Vire Length By Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes

Core & Coil (71A) MH ~LT~ 175W


Max Ballast-Lamp Distance Remote Wiring	10'
Recommended Fuse Value	3/3/2/2 A
Approval and Application	
Open Circuit Voltage Test (Volts)	228-280 V
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	A/A/A/A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029A

Product Data	
Order product name	CORE & COIL HID 71A5191001D
EAN/UPC - Product	781087082782
Order code	913701135901
Numerator - Quantity Per Pack	1
lumerator - Packs per outer box	1
Material Nr. (12NC)	913701135901
Net Weight (Piece)	2.228 kg

Dimensional drawing



MH BAL 50W M110 QUAD KIT





© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2016, February 1 - data subject to change