



Core & Coil (71A) MH ~LT~ 175W

CORE & COIL HID 71A5292500D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	M98-M143			
Lamp Type	70W MH			
Number Of Lamps	1 piece/unit			
Circuit Type	HX-HPF			
Ballast Type	Magnetic HID			
Base Model	71A5292			
Core Size	3 X 4 (2 LW)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI533-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	8 MFD			
Capacitor Catalog Number	7C080L30RA			
Capacitor Requirements	280V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.25 in			
Capacitor Height	2.75 in			
Automatic Restart	No			

Operating and Electrical			
Input Voltage	120/208/240/277 V		
Input Frequency	60 Hz		
Input Current (Open Circuit)	1.66/0.97/0.83/0.73 A		
Input Current (Starting)	0.71/0.41/0.4/0.3 A		
Input Current (Short Circuit)	0.65-0.98/0.4-0.6/0.32-0.49/0.29-0.44 A		
Secondary Short Circuit Current	1.03-1.26 A		
Constant Wattage Deviation	7%		
Ballast Factor (Nom)	1		
Power Factor (Nom)	0.90		
Open Circuit Voltage	255 V		
Input Current (Nom)	0.85/0.49/0.42/0.37 A A		
Input Power (Nom)	92 W		
Rated Lamp Power	70 W		
Wiring			
Wire Striplength	0.5 mm		
Wire Length By Color	12"		
Wire Type	Stranded		
Remote Wiring Configuration Allowed	Yes		


Datasheet, 2017, May 26 data subject to change

Core & Coil (71A) MH ~LT~ 175W

Max Ballast-Lamp Distance Remote Wiring	15'			
Recommended Fuse Value	4/3/2/2 A			
Approval and Application				
Open Circuit Voltage Test (Volts)	230-280 V			
Approval Marks	ULR CSA certificate RoHS Compliant			
Temperature Marking	A/A/A/A			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			
UL Temperature Code	1029A			

Product Data			
Order product name	CORE & COIL HID 71A5292500D		
EAN/UPC - Product	781087529256		
Order code	913700502581		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	6		
Material Nr. (12NC)	913700502581		
Net Weight (Piece)	2.282 kg		

Dimensional drawing



MH BAL 70W M98/143 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5292500D	2.88 in	1.44 in	3.9 in	3.5 in	2.8 in	2.4 in

