

# Core & Coil (71A) MH ~LT~ 175W

### **CORE & COIL HID 71A5390500D**

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	M90-M140			
Lamp Type	100W MH			
Number Of Lamps	1 piece/unit			
Circuit Type	HX-HPF			
Ballast Type	Magnetic HID			
Base Model	71A5390			
Core Size	3 X 4 (2 LW)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI533-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	12 MFD			
Capacitor Catalog Number	7C120M30RA			
Capacitor Requirements	280V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.65 in			
Capacitor Height	2.75 in			
Automatic Restart	No			

Operating and Electrical				
Input Voltage	120/208/240/277 V			
Input Frequency	60 Hz			
Input Current (Open Circuit)	2.5/1.5/1.3/1.12 A			
Input Current (Starting)	1.24/0.54/0.45/0.4 A			
Input Current (Short Circuit)	0.63-0.95/0.43-0.65/0.37-0.55/0.29-0.44 A			
Secondary Short Circuit Current	1.35-1.7 A			
Constant Wattage Deviation	12%			
Ballast Factor (Nom)	1			
Power Factor (Nom)	0.90			
Open Circuit Voltage	260 V			
Input Current (Nom)	1.15/0.66/0.58/0.5 A A			
Input Power (Nom)	129 W			
Rated Lamp Power	100 W			
Wiring				
Wire Striplength	0.5 mm			
Wire Length By Color	12"			
Wire Type	Stranded			
Remote Wiring Configuration Allowed	Yes			


Datasheet, 2017, May 26 data subject to change

# Core & Coil (71A) MH ~LT~ 175W

Max Ballast-Lamp Distance Remote Wiring	20'			
Recommended Fuse Value	10/5/5/4 A			
Approval and Application				
Open Circuit Voltage Test (Volts)	240-300 V			
Approval Marks	ULR CSA certificate RoHS Compliant			
Temperature Marking	B/B/A/A			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			
UL Temperature Code	1029B			

Product Data	
Order product name	CORE & COIL HID 71A5390500D
EAN/UPC - Product	781087539057
Order code	913700502681
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913700502681
Net Weight (Piece)	2.328 kg

## **Dimensional drawing**



MH BAL 100W M90/140 QUAD KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5390500D	3.07 in	1.5 in	3.9 in	3.5 in	2.8 in	2.4 in

