

Core & Coil (71A) MH ~LT~ 175W

CORE & COIL HID 71A5492500D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	M102-M142				
Lamp Type	150 MH				
Number Of Lamps	1 piece/unit				
Circuit Type	HX-HPF				
Ballast Type	Magnetic HID				
Base Model	71A5492				
Core Size	3 X 4 (2 LW)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI533-H4				
Ignitor Temperature Rating	105°C				
Capacitor Value	16 MFD				
Capacitor Catalog Number	7C160M30RA				
Capacitor Requirements	280V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval Dimensions	1.65 in				
Capacitor Height	2.75 in				
Automatic Restart	No				

Operating and Electrical						
Input Voltage	120/208/240/277 V					
Input Frequency	60 Hz					
Input Current (Open Circuit)	3.5/2.04/1.73/1.52 A					
Input Current (Starting)	1.75/1.3/0.85/0.77 A					
Input Current (Short Circuit)	1.03-1.41/0.61-0.92/0.49-0.74/0.44-0.67 A					
Secondary Short Circuit Current	2.05-2.55 A					
Constant Wattage Deviation	12%					
Ballast Factor (Nom)	1					
Power Factor (Nom)	0.90					
Open Circuit Voltage	250 V					
Input Current (Nom)	1.6/0.96/0.8/0.7 A A					
Input Power (Nom)	185 W					
Rated Lamp Power	150 W					
Wiring						
Wire Striplength	0.5 mm					
Wire Length By Color	12"					
Wire Type	Stranded					
Remote Wiring Configuration Allowed	Yes					


Datasheet, 2017, May 26 data subject to change

Core & Coil (71A) MH ~LT~ 175W

Max Ballast-Lamp Distance Remote	10'
Wiring	
Recommended Fuse Value	10/5/5/4 A
Approval and Application	
Open Circuit Voltage Test (Volts)	235-290 V
Approval Marks	ULR CSA certificate NOM certificate RoHS Compliant
Temperature Marking	C/B/B/A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)

UL Temperature Code	1029C				
Product Data					
Order product name	CORE & COIL HID 71A5492500D				
EAN/UPC - Product	781087549254				
Order code	913700572409				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	4				
Material Nr. (12NC)	913700572409				
Net Weight (Piece)	3.153 kg				

Dimensional drawing



MH BAL 150W M102/142 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5492500D	3.9 in	2.25 in	3.9 in	3.5 in	2.8 in	2.4 in

