
# **PHILIPS** Lighting



# Core & Coil (71A) MH ~LT~ 175W

## CORE & COIL HID 71A5493500D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information		
ANSI Code	M102-M142	_
Lamp Type	150 MH	_
Number Of Lamps	1 piece/unit	
Circuit Type	SUPER-CWA	
Ballast Type	Magnetic HID	
Base Model	71A5493	
Core Size	3 X 4 (2 coil)	
Suitable For Outdoor Use	Yes	
Ignitor Catalog Number	LI501-J4	
Ignitor Temperature Rating	105°C	
Capacitor Value	16 MFD	
Capacitor Catalog Number	7C160M30RA	
Capacitor Requirements	300V	
Capacitor Temperature Rating	105°C	
Capacitor Diameter/Oval Dimensions	1.65 in	
Capacitor Height	2.75 in	
Automatic Restart	No	


Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Input Current (Open Circuit)	1.98/1/0.95/0.81 A
Input Current (Starting)	0.7/0.39/0.37/0.31 A
Input Current (Short Circuit)	0.33-0.5/0.17-0.26/0.16-0.24/0.15-0.22 A
Secondary Short Circuit Current	1.9-2.35 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	217 V
Input Current (Nom)	1.64/0.92/0.85/0.73 A A
Input Power (Nom)	190 W
Rated Lamp Power	150 W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes

### Core & Coil (71A) MH ~LT~ 175W


Max Ballast-Lamp Distance Remote Wiring	5'
Recommended Fuse Value	5/2.5/2/2 A
Approval and Application	
Open Circuit Voltage Test (Volts)	195-239 V
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	D/C/D/C
UL Recognized	Yes
Hipot Test (1 Minute)	1500 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029D

Product Data	
Order product name	CORE & COIL HID 71A5493500D
EAN/UPC - Product	781087075470
Order code	913710676002
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710676002
Net Weight (Piece)	3.570 kg

#### **Dimensional drawing**



MH BAL 150W M102/142 QUAD C&C





© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2016, February 1 - data subject to change