



# Core & Coil (71A) MH 175W - 450W

## CORE & COIL HID 71A5741001D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

### Product data

General Information	
ANSI Code	M58
Lamp Type	250W MH
Number Of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	71A5741
Core Size	3 X 4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	NA
Ignitor Temperature Rating	NA
Capacitor Value	15 MFD
Capacitor Catalog Number	7C150P40R
Capacitor Requirements	400V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.75 in
Capacitor Height	3.75 in
Automatic Restart	No

Operating and Electrical	
Input Voltage	480 V
Input Frequency	60 Hz
Input Current (Open Circuit)	0.65 A
Input Current (Starting)	0.3 A
Input Current (Short Circuit)	0.25-0.35 A
Secondary Short Circuit Current	2-3 A
Constant Wattage Deviation	8%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	300 V
Input Current (Nom)	0.65 A A
Input Power (Nom)	298 W
Rated Lamp Power	250 W


Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes

## Core & Coil (71A) MH 175W - 450W

<b>Max Ballast-Lamp Distance Remote Wiring</b>	Determined by AWG used
<b>Recommended Fuse Value</b>	2 A
<b>Approval and Application</b>	
<b>Open Circuit Voltage Test (Volts)</b>	270-330 V
<b>Approval Marks</b>	ULR CSA certificate RoHS Compliant
<b>Temperature Marking</b>	H
<b>UL Recognized</b>	Yes
<b>Hipot Test (1 Minute)</b>	2000 V
<b>Hipot Test (2 Seconds)</b>	2500 V
<b>UL Insulation Class</b>	H(180°C)
<b>UL Temperature Code</b>	1029H

<b>Product Data</b>	
<b>Order product name</b>	CORE & COIL HID 71A5741001D
<b>EAN/UPC - Product</b>	781087096482
<b>Order code</b>	913700503391
<b>Numerator - Quantity Per Pack</b>	1
<b>Numerator - Packs per outer box</b>	1
<b>Material Nr. (12NC)</b>	913700503391
<b>Net Weight (Piece)</b>	4.478 kg

### Dimensional drawing



MH BAL 250W M58 480V KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5741001D	4.2 in	3 in	3.9 in	3.5 in	2.8 in	2.4 in

