

Core & Coil (71A) MH 175W - 450W

CORE & COIL HID 71A60A1001D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	M59			
Lamp Type	400W MH			
Number Of Lamps	1 piece/unit			
Circuit Type	CWA			
Ballast Type	Magnetic HID			
Base Model	71A60A1A			
Core Size	4 1/4 x 4 3/4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	NA			
Ignitor Temperature Rating	NA			
Capacitor Value	24 MFD			
Capacitor Catalog Number	7C240P40R			
Capacitor Requirements	400V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.75 in			
Capacitor Height	4.8 in			
Automatic Restart	No			

Operating and Electrical	
Input Voltage	120/277/347 V
Input Frequency	60 Hz
Input Current (Open Circuit)	2.6/1.2/0.9 A
Input Current (Starting)	2.6/1.2/0.9 A
Input Current (Short Circuit)	2.75-4.2/1.2-1.8/0.95-1.45 A
Secondary Short Circuit Current	3.5-4.3 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	300 V
Input Current (Nom)	4/1.75/1.4 A A
Input Power (Nom)	460 W
Rated Lamp Power	400 W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes


Datasheet, 2016, February 1 data subject to change

Core & Coil (71A) MH 175W - 450W

Max Ballast-Lamp Distance Remote Wiring	Determined by AWG used			
Recommended Fuse Value	10/5/4 A			
Approval and Application				
Open Circuit Voltage Test (Volts)	270-330 V			
Approval Marks	ULR CSA certificate RoHS Compliant			
Temperature Marking	D/D/D			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			
UL Temperature Code	1029D			

Product Data			
Order product name	CORE & COIL HID 71A60A1001E		
AN/UPC - Product	781087096659		
Order code	913700525509		
lumerator - Quantity Per Pack	1		
lumerator - Packs per outer box	1		
Material Nr. (12NC)	913700525509		
Net Weight (Piece)	5.884 kg		

Dimensional drawing



MH BAL 400W M59 120/277/347V KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A60A1001D	4 in	2.15 in	4.8 in	4.4 in	4.3 in	3.9 in

