

# Core & Coil (71A) MH ~GT~ 450W

## CORE & COIL HID 71A6792500A

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information		
ANSI Code	M48	
Lamp Type	1500W MH	
Number Of Lamps	1 piece/unit	
Circuit Type	CWA	
Ballast Type	Magnetic HID	
Base Model	71A6792A	
Core Size	4 1/4 x 6	
Suitable For Outdoor Use	Yes	
Ignitor Catalog Number	NA	
Ignitor Temperature Rating	NA	
Capacitor Value	32 MFD	
Capacitor Catalog Number	MD3202100	
Capacitor Requirements	525V	
Capacitor Temperature Rating	90°C	
Capacitor Diameter/Oval Dimensions	2 in	
Capacitor Height	3.75 in	
Automatic Restart	No	

Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Input Current (Open Circuit)	5.72/3.29/3.04/2.57 A
Input Current (Starting)	10.8/6.13/5.42/4.72 A
Input Current (Short Circuit)	9.1-13.6/5.22-7.83/4.56-6.84/3.96-5.95 V
Secondary Short Circuit Current	7.29-8.9 A
Constant Wattage Deviation	12%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	460 V
Input Current (Nom)	13.4/7.8/6.8/5.9 A A
Input Power (Nom)	1610 W
Rated Lamp Power	1500 W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes


Datasheet, 2017, May 26 data subject to change

# Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote Wiring	Determined by AWG used		
Recommended Fuse Value	30/25/20/15 A		
Approval and Application			
Open Circuit Voltage Test (Volts)	414-506 V		
Approval Marks	ULR CSA certificate RoHS Compliant		
Temperature Marking	G/E/E/G		
UL Recognized	Yes		
Hipot Test (1 Minute)	2000 V		
Hipot Test (2 Seconds)	2500 V		
UL Insulation Class	H(180°C)		
UL Temperature Code	1029G		

Product Data	
Order product name	CORE & COIL HID 71A6792500A
AN/UPC - Product	781087063514
Order code	913710652802
Numerator - Quantity Per Pack	1
lumerator - Packs per outer box	1
Material Nr. (12NC)	913710652802
Net Weight (Piece)	14.193 kg

## **Dimensional drawing**



MH BAL 1500W M48 QUAD C&C

Product	C1	C2	<b>A1</b>	A2	A3	B1	B2
CORE & COIL HID 71A6792500A	6.7 in	4.7 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in

