



Core & Coil (71A) HPS ~LT~ 200W

CORE & COIL HID 71A7807500DB

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information			
ANSI Code	S68		
Lamp Type	50W HPS		
Number Of Lamps	1 piece/unit		
Circuit Type	R-HPF		
Ballast Type	Magnetic HID		
Base Model	71A7807B		
Core Size	2 5/8 x 2 3/16		
Suitable For Outdoor Use	Yes		
Ignitor Catalog Number	INTEGRAL		
Ignitor Temperature Rating	125°C		
Capacitor Value	20 MFD		
Capacitor Catalog Number	7C200M12RA		
Capacitor Requirements	120V		
Capacitor Temperature Rating	105°C		
Capacitor Diameter/Oval Dimensions	1.25 in		
Capacitor Height	2.75 in		
Automatic Restart	No		

Operating and Electrical				
Input Voltage	120 V			
Input Frequency	60 Hz			
Power (Rated) (Nom)	50 W			
Input Current (Open Circuit)	0.9 A			
Input Current (Starting)	0.95 A			
Input Current (Short Circuit)	1.45-2.2 A			
Secondary Short Circuit Current	1.45-2.2 A			
Constant Wattage Deviation	Within Trapezoid			
Ballast Factor (Nom)	1			
Power Factor (Nom)	0.90			
Open Circuit Voltage	120 V			
Input Current (Nom)	0.55 A A			
Input Power (Nom)	62 W			
Rated Lamp Power	50W W			
Wiring				
Wire Striplength	0.5 mm			
Wire Length By Color	12"			
Wire Type	Stranded			


Datasheet, 2016, February 1 data subject to change

Core & Coil (71A) HPS ~LT~ 200W

Yes			
2'			
3 A			
114-126 V			
ULR CSA certificate RoHS Compliant			
A			
Yes			
2000 V			
2500 V			
H(180°C)			

UL Temperature Code	1029A	
Product Data		
Order product name	CORE & COIL HID 71A7807500DE	
EAN/UPC - Product	781087780749	
Order code	913700537809	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	8	
Material Nr. (12NC)	913700537809	
Net Weight (Piece)	0.704 kg	

Dimensional drawing



Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A7807500DB	2.7 in	0.95 in	2.6 in	2.2 in	2.2 in	1.8 in

