



F-can (72C)

F-CAN HID 72C52G2NP

The Philips Advance line of F-can HID ballasts comes in two dual-voltage configurations for the US and Canadian market. Ballasts for these luminaires are most often encased and potted in fluorescent ballast type cans.

Product data

General Information		Input Current (Nom)	
ANSI Code	M98(PULSESTART)		0.85/0.3 A A
Lamp Type	70W MH	Input Power (Nom)	94 W
Number Of Lamps	1 piece/unit	Rated Lamp Power	70 W
Circuit Type	HX-HPF	Wiring	
Ballast Type	Magnetic HID	Wire Striplength	0.5 mm
Base Model	72C52C2	Wire Length By Color	12"
Suitable For Outdoor Use	Yes	Wire Type	Stranded
Ignitor Catalog Number	Inside Can	Remote Wiring Configuration Allowed	Yes
Capacitor Catalog Number	Inside Can	Max Ballast-Lamp Distance Remote Wiring	20'
Automatic Restart	No	Recommended Fuse Value	5/2 A
Operating and Electrical		Mechanical and Housing	
Input Voltage	120/347 V	Housing Material	Metal
Input Frequency	60 Hz	Housing	F-Can
Input Current (Open Circuit)	1.7/0.7 A	Housing Dimensions	11.75 x 2.63 x 3.19
Input Current (Starting)	1.15/0.4 A	Approval and Application	
Input Current (Short Circuit)	0.5-0.75/0.25-0.4 A	Open Circuit Voltage Test (Volts)	215-265 V
Secondary Short Circuit Current	0.95-1.2 A	Approval Marks	CSA certificate RoHS Compliant
Constant Wattage Deviation	10%	Temperature Marking	90°C max. case
Ballast Factor (Nom)	1	UL Recognized	No
Power Factor (Nom)	0.90	Hipot Test (1 Minute)	1700 V
Open Circuit Voltage	255 V		

F-can (72C)


Hipot Test (2 Seconds)	2100 V
UL Insulation Class	A(105°C)
UL Temperature Code	NA

Product Data

Order product name	F-CAN HID 72C52C2NP
EAN/UPC - Product	781087007600

Order code	913700579809
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913700579809
Net Weight (Piece)	3.970 kg

Dimensional drawing



MH BAL 70W M98/143 120/347V FCAN

Product	A1	A2	A3	B1	B2	C1	D1
F-CAN HID 72C52C2NP	12 in	11.13 in	10.5 in	3.9 in	2.0 in	2.6 in	0.3 in

