



Encapsulated Core & Coil (73B)

ENCAPSULATED CORE & COIL HID 73B5591500DEE

Where quiet performance is required, the standard open core and coil ballast is encapsulated (potted) in a cube-shaped steel can utilizing Class H (180°C) polyester compound.

Product data


General Information			
ANSI Code	M137-M152	Input Frequency	60 Hz
Lamp Type	175W MH	Input Current (Open Circuit)	1.5/0.83/0.75/0.63 A
Number Of Lamps	1 piece/unit	Input Current (Starting)	0.67/0.39/0.33/0.28 A
Circuit Type	SUPER-CWA	Input Current (Short Circuit)	0.54-0.8/0.31-0.47/0.26-0.4/0.23-0.34 A
Ballast Type	Magnetic HID	Secondary Short Circuit Current	1.56-1.91 A
Base Model	73B5591EE	Constant Wattage Deviation	10%
Suitable For Outdoor Use	Yes	Ballast Factor (Nom)	1
Ignitor Catalog Number	LI533-H4	Power Factor (Nom)	0.90
Ignitor Temperature Rating	105°C	Open Circuit Voltage	280 V
Capacitor Value	11 MFD	Input Current (Nom)	1.66/0.95/0.83/0.71 A A
Capacitor Catalog Number	7C110M40	Input Power (Nom)	198 W
Capacitor Requirements	370V	Rated Lamp Power	175 W
Capacitor Temperature Rating	105°C	Wiring	
Capacitor Diameter/Oval Dimensions	1.65000000 in	Wire Striplength	0.5 mm
Capacitor Height	3.75 in	Wire Length By Color	12"
Automatic Restart	No	Wire Type	Stranded
Operating and Electrical		Remote Wiring Configuration Allowed	Yes
Input Voltage	120/208/240/277 V	Max Ballast-Lamp Distance Remote	2'
		Wiring	

Encapsulated Core & Coil (73B)

Recommended Fuse Value	5/3/3/2 A
Mechanical and Housing	
Housing Material	Metal
Housing	Encap
Housing Dimensions	5.4" x 5.0" x 3.8"
Approval and Application	
Open Circuit Voltage Test (Volts)	250-300 V
Approval Marks	ULR CSA certificate EISA RoHS Compliant
Temperature Marking	A/A/A/A
Hum And Noise Level	A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	25000 V

UL Insulation Class	H(180°C)
UL Temperature Code	1029A
Product Data	
Order product name	ENCAPSULATED CORE & COIL HID
	73B5591500DEE
EAN/UPC - Product	781087081013
Order code	913701102502
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	913701102502
Net Weight (Piece)	6.909 kg

Dimensional drawing



MH BAL 175W M137/M152 QUAD ENCAP

Product	A1	A2	A3	B1	B2	C1	D1
ENCAPSULATED CORE & COIL HID	6.75 in	6 in	5.4 in	3.8 in	2 in	5 in	0.25 in
73B5591500DEE							

