



# Indoor Enclosed (78E)

## **INDOOR ENCLOSED HID 78E6041001**

These units are designed for use indoors where the ballast must be mounted remotely from the luminaire. These ballasts are typically used in applications where the luminaire is mounted in an area with very high ambient temperatures. The ballast can be mounted remotely in a cooler location.

#### **Product data**

General Information	
ANSI Code	M59
Lamp Type	400W MH
Number Of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	78E6041
Suitable For Outdoor Use	No
Ignitor Catalog Number	NA
Capacitor Catalog Number	Inside Can
Automatic Restart	No
Operating and Electrical	
Input Voltage	480 V
Input Frequency	60 Hz
Input Current (Open Circuit)	0.75 A
Input Current (Starting)	0.9 A
Input Current (Short Circuit)	0.6-0.95 A
Secondary Short Circuit Current	3.5-4.3 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90

Open Circuit Voltage	300 V						
Input Current (Nom)	1 A A						
Input Power (Nom)	462 W						
Rated Lamp Power	400 W						
Wiring							
Wire Striplength	0.5 mm						
Wire Length By Color	12"						
Wire Type	Stranded						
Remote Wiring Configuration Allowed	Yes						
Max Ballast-Lamp Distance Remote Wiring	Determined by AWG used						
Recommended Fuse Value	3 A						
Mechanical and Housing							
Housing Material	Metal						
Housing	IE						
Housing Dimensions	14.44" x 5.75" x 7.69"						
Approval and Application							
Open Circuit Voltage Test (Volts)	270-330 V						
Approval Marks	UL certificate RoHS Compliant						
Temperature Marking	Max. ambient temperature 55°C						


Datasheet, 2016, February 1 data subject to change

## Indoor Enclosed (78E)

UL Recognized	No
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	NA
Product Data	
Order product name	INDOOR ENCLOSED HID 78E6041001

EAN/UPC - Product	781087860410				
Order code	913700547909				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	1				
Material Nr. (12NC)	913700547909				
Net Weight (Piece)	14.738 kg				

### **Dimensional drawing**



MH BAL 400W M59 480V ENCL

Product	A1	A2	A3	A4	B1	B2	C1	D1
INDOOR ENCLOSED HID	14.4 in	13.4 in	12.7 in	12.1 in	7.7 in	3.3 in	5.8 in	0.4 in
78E6041001								

