

# Outdoor Weatherproof (79W)

# **OUTDOOR WEATHERPROOF HID 79W5790001**

Outdoor weatherproof ballasts are designed for remote mounting outdoors under all weather conditions. They may also be placed inside a pole base, but care must be taken to avoid areas prone to flood situations as they are not water submersable.

### **Product data**

| General Information             |                                     |
|---------------------------------|-------------------------------------|
| ANSI Code                       | M58                                 |
| Lamp Type                       | MH                                  |
| Number Of Lamps                 | 1 piece/unit                        |
| Circuit Type                    | CWA                                 |
| Ballast Type                    | Magnetic HID                        |
| Base Model                      | 79W5790                             |
| Suitable For Outdoor Use        | Yes                                 |
| Ignitor Catalog Number          | Inside Can                          |
| Capacitor Catalog Number        | Inside Can                          |
| Automatic Restart               | No                                  |
|                                 |                                     |
| Operating and Electrical        |                                     |
| Input Voltage                   | 120/208/240/277 V                   |
| Input Frequency                 | 60 Hz                               |
| Input Current (Open Circuit)    | 1.55/0.95/0.85/0.7 A                |
| Input Current (Starting)        | 2.1/1.4/1.1/1 A                     |
| Input Current (Short Circuit)   | 1.7-2.5/1.1-1.7/0.95-1.35/0.8-1.2 A |
| Secondary Short Circuit Current | 2.25-2.75 A                         |
| Constant Wattage Deviation      | 10%                                 |
|                                 |                                     |

| Ballast Factor (Nom)                    | 1                      |
|---|------------------------|
| Power Factor (Nom)                      | 0.90                   |
| Open Circuit Voltage                    | 310 V                  |
| Input Current (Nom)                     | 2.5/1.45/1.25/1.1 A A  |
| Input Power (Nom)                       | 285 W                  |
| Rated Lamp Power                        | 250 W                  |
|   |                        |
| Wiring                                  |                        |
| Wire Striplength                        | 0.5 mm                 |
| Wire Length By Color                    | 10"                    |
| Wire Type                               | Stranded               |
| Remote Wiring Configuration Allowed     | Yes                    |
| Max Ballast-Lamp Distance Remote Wiring | Determined by AWG used |
| Recommended Fuse Value                  | 8/5/5/3 A              |
|   |                        |
| Mechanical and Housing                  |                        |
| Housing Material                        | Metal                  |
| Housing                                 | OW                     |
| Housing Dimensions                      | 8.6" x 6.38" x 6.38"   |
|   |                        |


Datasheet, 2016, February 1 data subject to change

# Outdoor Weatherproof (79W)

| Approval and Application          |   |  |  |  |
|-----------------------------------|---|--|--|--|
| Open Circuit Voltage Test (Volts) | 280-340 V                                   |  |  |  |
| Approval Marks                    | CSA certificate UL certificate RoHS Complia |  |  |  |
| Temperature Marking               | Max. case temperature 90°C                  |  |  |  |
| UL Recognized                     | No  |  |  |  |
| Hipot Test (1 Minute)             | 2000 V                                      |  |  |  |
| Hipot Test (2 Seconds)            | 2500 V                                      |  |  |  |
| UL Insulation Class               | H(180°C)                                    |  |  |  |
| UL Temperature Code               | NA  |  |  |  |

| Product Data                    |                                    |  |  |  |  |
|---------------------------------|------------------------------------|--|--|--|--|
| Order product name              | OUTDOOR WEATHERPROOF HID 79W579000 |  |  |  |  |
| EAN/UPC - Product               | 781087957905                       |  |  |  |  |
| Order code                      | 913700583709                       |  |  |  |  |
| Numerator - Quantity Per Pack   | 1                                  |  |  |  |  |
| Numerator - Packs per outer box | 1                                  |  |  |  |  |
| Material Nr. (12NC)             | 913700583709                       |  |  |  |  |
| Net Weight (Piece)              | 6.482 kg                           |  |  |  |  |

## **Dimensional drawing**



MH BAL 250W M58 QUAD WP

| Product                             | B1     | B2     | В3   | C1     | C2     |
|-------------------------------------|--------|--------|------|--------|--------|
| OUTDOOR WEATHERPROOF HID 79W5790001 | 7.3 in | 6 4 in | 1 in | 8 6 in | 1.9 in |

