



Outdoor Weatherproof (79W)

OUTDOOR WEATHERPROOF HID 79W6586001

Outdoor weatherproof ballasts are designed for remote mounting outdoors under all weather conditions. They may also be placed inside a pole base, but care must be taken to avoid areas prone to flood situations as they are not water submersable.

Product data


General Information			
ANSI Code	CSI	Ballast Factor (Nom)	1
Lamp Type	MH	Power Factor (Nom)	0.90
Number Of Lamps	1 piece/unit	Open Circuit Voltage	200 V
Circuit Type	CWA	Input Current (Nom)	9.8/4.2 A A
Ballast Type	Magnetic HID	Input Power (Nom)	1150 W
Base Model	79W6586	Rated Lamp Power	1000 W
Suitable For Outdoor Use	Yes	Wiring	
Ignitor Catalog Number	Inside Can	Wire Striplength	0.5 mm
Capacitor Catalog Number	Inside Can	Wire Length By Color	10"
Automatic Restart	No	Wire Type	Stranded
Operating and Electrical		Remote Wiring Configuration Allowed	Yes
Input Voltage	120/277 V	Max Ballast-Lamp Distance Remote Wiring	NA
Input Frequency	60 Hz	Recommended Fuse Value	25/15 A
Input Current (Open Circuit)	9.4/4.0 A	Mechanical and Housing	
Input Current (Starting)	8.5/3.6 A	Housing Material	Metal
Input Current (Short Circuit)	6.1-9.1/2.6-4.0 A	Housing	OW
Secondary Short Circuit Current	15-23 A	Housing Dimensions	13.8" x 6.38" x 6.38"
Constant Wattage Deviation	10%		

Outdoor Weatherproof (79W)

Approval and Application	
Open Circuit Voltage Test (Volts)	180-220 V
Approval Marks	UL certificate RoHS Compliant
Temperature Marking	Max. case temperature 90°C
UL Recognized	No
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	NA

Product Data	
Order product name	OUTDOOR WEATHERPROOF HID 79W6586001
EAN/UPC - Product	781087010082
Order code	913700506591
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	913700506591
Net Weight (Piece)	20.752 kg

Dimensional drawing



MH BAL 1000W CSI 120/277V WP

Product	B1	B2	B3	C1	C2
OUTDOOR WEATHERPROOF HID 79W6586001	7.3 in	6.4 in	1 in	13.8 in	1.9 in

