

SmartMate

SMARTMATE ICF2S18M1BS35M

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

Product data

General Information				
Lamp Type	CFQ18W/G24Q			
Number Of Lamps	1/2 piece/unit			
Ballast Type	Electronic Fluorescent			
Base Model	ICF2S18M1BS			
Suitable For Outdoor Use	Yes			
Automatic Restart	Yes			
Operating and Electrical				
Input Voltage	120 to 277 V			
Input Frequency	50 to 60 Hz			
Total Harmonic Distortion USA	10 %			
Ignition Method	Programmed Start			
Crestfactor (Nom)	1.5			
Ignition Time (Nom)	1.5 s			
Ballast Factor (Nom)	0.95			
Power Factor (Nom)	0.98			
Input Current (Max)	0.30 A			
Input Current (Min)	0.13 A			
Input Power (Nom)	35-35 W			

Rated Lamp Power	18 W		
Wiring			
Color Input Terminals	Black and White		
Color Output Terminals	RED, YEL & BLU		
Wire Striplength	0.375 mm		
Lamp Connection	Series		
Wire Length By Color	No wires		
Wire Gauge (Nom)	18AWG mm		
Wire Type	Solid Yes		
Remote Wiring Configuration Allowed	Yes		
Tandem Wiring Configuration Allowed	Yes		
Through Wiring Configuration Allowed	Yes		
Max Ballast-Lamp Distance Remote Wiring	1-L = 15' / 2-L = 6'		
Max Ballast-Lamp Distance Tandem Wiring	2-L: Red = 6'		
Max Ballast-Lamp Distance Through Wiring	2-L: Red = 6'		
Connector Type	Poke-In		
Temperature	·		
T-Case Maximum (Nom)	75 °C		


Datasheet, 2017, May 26 data subject to change

SmartMate

Mechanical and Housing	
Housing Material	Metal
Housing	M1
Housing Dimensions	4.98" x 2.4" x 0.98"
Approval and Application	
EMC Immunity Standard	FCC Non-Consumer
Approval Marks	CSA certificate UL certificate CEC Listing RoHS
	Compliant
Hum And Noise Level	A
UL Recognized	No

Product Data			
Order product name	SMARTMATE ICF2S18M1BS35M		
EAN/UPC - Product	781087108291		
Order code	913700532301		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	16		
Material Nr. (12NC)	913700532301		
Net Weight (Piece)	0.207 kg		

Dimensional drawing



ELE BALLAST (2) 18W CFL (4-PIN) 120-277V

Product	A1	A2	A3	B1	C1
SMARTMATE ICF2S18M1BS35M	4.60 in	4.20 in	2.00 in	2.40 in	0.98 in

