



e-Vision Low Wattage 20-150W

E-VISION IMH39KLFSM

Low frequency electronic HID ballasts such as the Philips Advance e-Vision line constantly measure and adjust the wattage, optimizing delivery of the ceramic lamps' superior color properties. This makes ceramic metal halide operated by e-Vision ballasts the premier choice for many applications previously illuminated by either tungsten halogen or incandescent sources, such as retail lighting.

Product data

General Information	
ANSI Code	C130-M130
Lamp Type	39W MH
Number Of Lamps	1 piece/unit
Ballast Type	Electronic HID
Base Model	IMH39KLFS
Suitable For Outdoor Use	Yes
Operating and Electrical	
Input Voltage	120 to 277 V
Input Frequency	50 to 60 Hz
Total Harmonic Distortion USA	15 %
Crestfactor (Nom)	1.8
Ignition Time (Nom)	1200 s
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Input Current (Max)	0.39 A
Input Current (Min)	0.18 A

Input Power (Nom)	45 W
Rated Lamp Power	39 W
Wiring	
Color Input Terminals	No terminals
Color Output Terminals	No terminals
Wire Striplength	0.50 mm
Control Wire Gauge	NA
Wire Length By Color	Input=6" Output=13"
Wire Gauge (Nom)	18AWG mm
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	No
Through Wiring Configuration Allowed	No
Connector Type	No connector


Datasheet, 2016, February 1 data subject to change

e-Vision Low Wattage 20-150W

Temperature					
T-Case Maximum (Nom)	90 °C				
Mechanical and Housing					
Housing Material	Metal				
Housing	К				
Housing Dimensions	4.1" x 1.3" x 1.2"				
Approval and Application					
EMC Immunity Standard	FCC Non-Consumer				
Approval Marks	CSA certificate UL certificate RoHS Compliant				
Hum And Noise Level	A				

UL Recognized	No		
Product Data			
Order product name	E-VISION IMH39KLFSM		
EAN/UPC - Product	781087124260		
Order code	913701243802		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	12		
Material Nr. (12NC)	913701243802		
Net Weight (Piece)	178.000 g		

Dimensional drawing



E-VISION IMH39KLFSM

Product	A1	A2	A3	B1	B2	C1
E-VISION IMH39KLFSM	4.4 in	4.1 in	4.5 in	1.1 in	0.5 in	1.2 in

