


The "Ultimate" Electronic Sign Ballast

For use with 800mA T12 HO, T8 HO ANSI Standard, T8 Long-Life and Slim-Line Lamps

EESB Series
EESB-0250-16L-120-277V



Replaces 10 Existing Ballasts

- Operates one to six lamps, from 2 to 50 feet with just one ballast
- For use with 800mA T12 HO, T8 HO ANSI Standard, T8 Long-Life and Slim-Line Lamps
- Title 24 Compliant 
- Input Voltages From 120-277 VAC 50-60 Hz
- Reliable Cold Weather Starting To -20° F
- High PF / Thermally Protected Outdoor Type 2 Ballast
- Increased Lamp Life
- Energy Savings
- Replaces 10 Existing Ballasts
- Less Inventory, More Flexibility



ENERGY SAVINGS
LOOK FOR THIS MARK SIGNIFYING
ENERGY SAVING PRODUCTS
FROM ALLANSON/
LIGHTING COMPONENTS

EESB-11-10



Fluorescent

The "Ultimate" Electronic Sign Ballast

Features	Benefits
■ Meets ANSI C85.11 Standards	■ RED and BLUE Wiring Reduces Installation Labor
■ Sound Rated 'A'	■ Quiet Operation In All Installation Conditions
■ Meets FCC Rating / UL & CSA	■ Low RFI and EMI Ensures No Interference Issues
■ Multiple Lamp Combination	■ Less Than 8% THD For Installation Confidence
■ Four Year Warranty	■ Operates 1 to 6 lamps

Specifications			
Number of Lamps	Lamp type	Input Current @ 120V	Input Current @ 277V
6	F96T8HO	3.65A	1.75A
6	F96T8HO Long Life	3.55A	1.65A
5	F120T12HO	3.54A	1.65A
6	F96T12HO	3.10A	1.50A
4	F96T8HO Long Life	2.65A	1.30A
2	F96T12HO	1.65A	0.82A
1	F48T12HO	0.52A	0.30A
1	F24T12HO	0.32A	0.25A

Ballast Case Dimensions		
Length	Width	Height
14 7/16"	3"	2 3/4"

Visit us at www.allanson.com / www.eballast.com