



- > Energy Saving 8 Watt Integrated LED
- > Uses 85% Less Energy than Equivalent 65 Watt Incandescent Bulb
- > Bright White 3000K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > IC Rated for Direct Contact with Insulation

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

4" AC Power Recessed Downlight

625 lm | 120VAC | Model 53182211 | Part DL-4-625-830-SV-D



SPECIFICATIONS

Model	53182211
Part	DL-4-625-830-SV-D
Description	4" AC Power Recessed Retrofit Downlight Kit
Input Voltage (VAC)	120
Wattage	8
Dimmability	Triac
Average Rated Life ¹	50,000 hours
Typical Lumens ²	625
CCT ³	3000K
Location Rating	UL Wet
CRI ⁴	80
Beam Angle	100
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	10
DUV	-0.0008
CBCP	289
Operating Frequency (Hz)	60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra





4" AC Power Recessed Downlight

625 lm | 120VAC | Model 53182211 | Part DL-4-625-830-SV-D

SHIPPING INFORMATION

Model	53182211
Part	DL-4-625-830-SV-D
UPC	849489003535
Product Dimensions (W x H in.)	4 7/8 x 1 5/8
Product Dimensions (W x H cm.)	12 1/2 x 4
Product Weight (lbs.)	0.25
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489003554
Master Carton Dimensions (L x W x H in.)	6.46 x 8.03 x 6.3
Master Carton Dimensions (L x W x H cm.)	16.4 x 20.4 x 16
Master Carton Weight (lbs)	2.03
Pallet Quantity	1008

COMPATIBILITY

Dimmers:

Lutron: CT-603PGH-WH, GL-600H-DK, MSCL-OP153M, MACL-153MH-WH, SCL-153PR-WH, TGCL-153PR-WH, TGCL-153PH-WH, TG-603PGH-WH, AYCL-153P-WH
Leviton: CD-C22-06672-12A, CD-R62-06674-12A, CD-R50-IPL06-12A, SB-011-IPL06-22A, 8100-I
Legrand: ADWR703HW4, ADPD453LM2
Cooper: DLC03PA-PTA, 9573A-PTA

Cans:

Commercial Electric: H9, H10, H13
Juno: IC1, IC91, IC1R
Halo: H99TAT, H99RTAT, H99ICAT

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256