# Presented By: BulbsDepot Contact Phone: Customer Name: Project Name:



## 14682 - GE Lucalox® High Pressure Sodium ED37

LU750

Contact E-mail

## **PRODUCT PHOTO**



## **GENERAL CHARACTERISTICS**

Fixture Type:

Base Description Mogul Screw
Base Type Screw-In

Lamp Enclosure Type (LET) Open or enclosed fixtures

Mercury-Picogrm per mean Im hr
Rated Life Hours-nominal 24000 h
Bulb Finishes and Colors Clear
Mercury Content EMEA ONLY 22.27
Bulb Material Hard glass

Product Technology High Intensity Discharge

Lamp Count1Life in Years21.91Requested StructureSleeveBaseE39Bulb ShapeED37

## PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal99000 lmNominal Lumens per Watt147 lmInitial Lumens-nominal110000 lmColor Rendering Index-CRI22Color Temperature2100 K

## **PRODUCT INFORMATION**

Product Code 14682

Description LU750

Alternative Unit Of Measure CASE

Standard Package Quantity 6

Ean UPC 043168146821 Standard Package GTIN 10043168146828

No Of Items Per Sales Unit

No Of Items Per Standard Package 6
Sales Unit Case

UCC 043168146821

Alternative Unit Of Measure EACH
Standard Package Quantity 1

Ean UPC 043168146821 Standard Package GTIN 00043168146821

No Of Items Per Sales Unit 1
No Of Items Per Standard Package 1
Sales Unit Fach

UCC 043168146821

# **DIMENSIONS**

Diameter 4.62 in Light Center Length Millimeter 6.75 in Nominal Length 11.5 in

## **ELECTRICAL CHARACTERISTICS**

Burn Position Universal burning position

Estimated Energy Cost per Year 90.33 Rated power (Watts) 750 W

## **CAUTIONS & WARNINGS**

WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: http://www.fda.gov/cdrh/radhealth/products/urburns.html

Contains sodium? chemical burn risk

Avoid skin contact with broken pieces.

#### Caution

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use excessive force when installing lamp.

Do not use lamp if outer glass is scratched or broken.

Wear safety glasses and gloves when handling lamp.

#### Risk of Burn

Allow lamp to cool before handling.

Do not turn on lamp until fully installed.

# Risk of Electric Shock

Do not use where directly exposed to water or outdoors without an enclosed fixture.

Turn power off before inspection

installation or removal.

#### Risk of Fire

Keep combustible materials away from lamp.

Use fused or thermally protected ballast - see instructions.

Use in fixture rated for this product.


Unexpected lamp rupture may cause injury, fire, or property damage


Do not store flammable materials near/below S-rated lamp in open fixture

Do not turn on lamp until fully installed.

Do not use lamp if outer glass is scratched or broken.

Do not use where directly exposed to water or outdoors without an enclosed fixture.





Feb 6, 2021 9:52:11 PM | For additional information, visit https://products.gecurrent.com/





Lamp Contains Mercury

Manage in Accord with Disposal Laws

See: www.lamprecycle.org or 1-800-327-0097