Contact Phone: Contact E-mail:




GE Lighting

19876 - 35PAR36/H/SP8

GE PAR36 - Narrow Spot

• Standard Halogen - Crisp, white light







CAUTIONS & WARNINGS

Caution

· Lamp may shatter and cause injury if broken

- Do not use lamp if outer glass is scratched or broken.

Warning

Risk of Burn

- Allow lamp/fixture to cool before handling.
- A damaged lamp emits UV radiation which may cause eye/skin injury
- Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage - Do not exceed 110% of rated voltage.
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in fixture rated for this product.

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Sealed Beam - PAR
PAR36
Screw Terminals
C-6
4000.0 h
Narrow Spot

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 250.0 Beam Spread (NOM) 8.0° Beam Spread - Horizontal 11.0 - 10.0 ° Beam Spread - Vertical 9.0 - 10.0 ° Center Beam Candlepower 8000.0 (CBCP) (NOM) Color Temperature (NOM) 3050.0 K Max. Beam Candlepower 8000.0 (MBCP) (MAX) Nominal Initial Lumens per Watt 7.142857 (NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 35.0 Voltage (NOM) 12.0

DIMENSIONS

2.750 in(69.8 mm) Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM) 4.500 in(114.3 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168970280