Contact Phone: Contact E-mail:




GE Lighting

19877 - 35PAR36/H/FL30

GE PAR36 - Wide Flood

Standard Halogen - Crisp, white light







CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

- Do not use lamp if outer glass is scratched or broken.

Warning

Risk of Burn

- Allow lamp/fixture to cool before handling.

 \bullet A damaged lamp emits UV radiation which may cause eye/skin injury

- Turn power off if glass bulb is broken. Remove and dispose of lamp.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
Do not exceed 110% of rated voltage.

- Do not use lamp if outer glass is scratched or broken.

Risk of Fire

- Keep combustible materials away from lamp.

- Use in fixture rated for this product.

GENERAL CHARACTERISTICS

Customer Name:

Project Name: Fixture Type:

Lamp Type	Sealed Beam - PAR
Bulb	PAR36
Base	Screw Terminals
Filament	C-6
Rated Life (NOM)	4000.0 h
Primary Application	Wide Flood
Base Filament Rated Life (NOM)	Screw Terminals C-6 4000.0 h

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 250.0 Beam Spread (NOM) 30.0 ° Beam Spread - Horizontal 40.0 - 10.0 ° Beam Spread - Vertical 34.0 - 10.0 ° Center Beam Candlepower 900.0 (CBCP) (NOM) Color Temperature (NOM) 3050.0 K Max. Beam Candlepower 900.0 (MBCP) (MAX) Nominal Initial Lumens per Watt 7.142857 (NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM)35.0Voltage (NOM)120.0

DIMENSIONS

Maximum Overall Length
(MOL) (NOM)2.750 in(69.8 mm)Bulb Diameter (DIA) (NOM)4.500 in(114.3 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168970297