

22660 - GE Starcoat® T8

F40T8/SPX30

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	8 mg
Mercury-Picogram per mean lm hr	119.4
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Soda lime
Rated Life Hours-nominal	20000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	3350 lm
Nominal Initial Lumen per Watt	93
Color Rendering Index-CRI	84

PRODUCT INFORMATION

Product Code	22660
Description	F40T8/SPX30
Alternative Unit Of Measure	CASE
Standard Package Quantity	24
Ean UPC	043168226608
Standard Package GTIN	10043168226605
No Of Items Per Sales Unit	
No Of Items Per Standard Package	24
Sales Unit	Case
UCC	043168226608
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168226608
Standard Package GTIN	00043168226608
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	

DIMENSIONS

Bulb Diameter (DIA) <Max>	1.1 in
Bulb Diameter (DIA) <Min>	0.94 in
Diameter	1.0 in
End of Base Pin to Pin	59.5 in
Face to End of Opposing Pin (B) <Max>	59.33 in
Face to End of Opposing Pin (B) <Min>	59.24 in
Nominal Length	60.0 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Open Circuit Voltage (rapid start) Min @ Temperature	385.00 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Rated power (Watts)	40 W

CAUTIONS & WARNINGS




Caution

- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning

- Risk of Electric Shock
- Turn power off before inspection

installation or removal.



Mar 12, 2021 9:49:44 PM | For additional information, visit <https://products.gecurrent.com/>



Lamp Contains Mercury

Manage in Accord with Disposal Laws

See : www.lamprecycle.org or 1-800-327-0097