

**33893 - GE garage & basement circline 40 watt T9 circline 1-pack
FC16T9/CW**

- ☞ Ideal for office and utility use
- ☞ Lasts up to 8 years!
- ☞ 1.1 inch diameter T9 circline with 4-pin (g10q) base
- ☞ 4100K cool white light appearance
- ☞ Cool white light perfect for sizable spaces
- ☞ For use in large spaces such as basements and garages
- ☞ GE garage & basement circline fluorescent bulbs' cool white light is perfect for illuminating sizable spaces throughout your home. Use in large open spaces in your home including finished and unfinished basements, garages and rec rooms
- ☞ Lasts 5.5 years based on 6 hours per day usage

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	4-Pin (G10q)
Base Type	Pin/Plug-In
Mercury Content	7 mg
Mercury-Picogram per mean lm hr	287.4
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Lead glass
Rated Life Hours-nominal	12000 h
Primary Application	Full Wattage Garage & Basement
Product Technology	Linear Fluorescent
Base	G10q
Bulb Shape	T9

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2030 lm
Nominal Initial Lumen per Watt	67.5
Initial Lumens-nominal	2700 lm
Color Temperature	4100 K

PRODUCT INFORMATION

Product Code	33893
Description	FC16T9/CW
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168981002
Standard Package GTIN	00043168981002
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168338936
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168981002
Standard Package GTIN	00043168338936
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168338936
Alternative Unit Of Measure	CASE
Standard Package Quantity	0
Ean UPC	043168981002
Standard Package GTIN	00338936
No Of Items Per Sales Unit	
No Of Items Per Standard Package	0
Sales Unit	Case
UCC	

DIMENSIONS

Bulb Diameter (DIA) <Max>	1.22 in
Bulb Diameter (DIA) <Min>	1.03 in
Diameter	1.12 in
Nominal Length	16.0 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Open Circuit Voltage (rapid start) Min @ Temperature	205.00 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Input Voltage [nom]	109 W
Rated power (Watts)	40 W

CAUTIONS & WARNINGS



Warning

Risk of Electric Shock

Turn power off before inspection
installation or removal.

Caution

Lamp may shatter and cause injury if broken
Wear safety glasses and gloves when handling lamp.
Do not use excessive force when installing lamp.



Apr 16, 2021 6:51:45 PM | For additional information, visit <https://products.gecurrent.com/>



Lamp Contains Mercury

Manage in Accord with Disposal Laws

See : www.lamprecycle.org or 1-800-327-0097