

# Illuminate



Application illustration only, subject lamps not used in photo.



## LED A-Line general purpose lamps

GE offers dimmable LED A-Line lamps as excellent replacements for standard 25-watt, 40-watt, 60-watt, 75-watt and 100-watt incandescent lamps.

### LOW-COST OPERATION

- For example, a 100-watt incandescent replacement lamp using 13 watts of energy and producing 800 lumens can save over \$129 in energy costs over the rated life of the lamp versus a standard 840 lumen, 60-watt incandescent A19 based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent or halogen light sources

### EXCELLENT COLOR RENDERING

- Available with a CRI of 78 - 80

### COLOR TEMPERATURE

- Halogen-like color
- Available in 2400K, 2700K, 3000K, 4000K and 5000K

### LONG LIFE

- Up to 25,000 hours rated life (L70)

### DIMMABLE

- Dims from 100% to as low as 10%

### ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

### GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: <http://products.currentbyge.com>.

ecomagination<sup>SM</sup>






Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

**current**  
powered by GE



## LED A-Line general purpose lamps

### A-Line Lamps

| Bulb Shape  | Base Type | Watts | Order Code | Description      | Volts            | Case Qty** | MOL (in) | Lumens Initial | CBCP         | Initial Color Temp | CRI  | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|---|-----------|-------|------------|------------------|------------------|------------|----------|----------------|--------------|--------------------|------|---------------------|-----------------------|----------|---------------------|------------------|------------------------|
| A-15  |           |       |            |                  |                  |            |          |                |              |                    |      |                     |                       |          |                     |                  |                        |
|  | MED       | 4     | 34038      | LED4DA15-W3/827  | 120              | 6          | 3.5      | 300            |              | 2700               | 80   | 40W                 | 15,000                | Yes      |                     | Damp             | White                  |
|   |           |       | 34051      | LED4DA15-C3/827  | 120              | 6          | 3.5      | 300            |              | 2700               | 80   | 40W                 | 15,000                | Yes      |                     | Damp             | Clear                  |
| A-19  |           |       |            |                  |                  |            |          |                |              |                    |      |                     |                       |          |                     |                  |                        |
|  | MED       | 6     | 69115      | LED6DA19/827     | 120              | 6          | 4.4      | 480            |              | 2700               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |
|   |           |       | 69118      | LED6DA19/830     | 120              | 6          | 4.4      | 480            |              | 3000               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |
|   |           |       | 69132      | LED6DA19/840     | 120              | 6          | 4.4      | 480            |              | 4000               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |
|   |           |       | 69144      | LED6DA19/850     | 120              | 6          | 4.4      | 480            |              | 5000               | 80   | 40W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |
|  | 7         |       | 95928      | LED7DAV3/5K      | 120              | 6          | 4.6      | 500            |              | 5000               | 80   | 40W                 | 25,000                | Yes      |                     | Damp             | White, Semi-Omni       |
|   |           |       | 34238      | LED7DA19/824     | 120              | 6          | 4.44     | 450            |              | 2400               | 80   | 40W                 | 25000                 | Yes      |                     | Damp             | White                  |
|   | 10        |       | 69117      | LED10DA19/827    | 120              | 6          | 4.4      | 800            |              | 2700               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |
|   |           |       | 69119      | LED10DA19/830    | 120              | 6          | 4.4      | 800            |              | 3000               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |
|   |           |       | 69133      | LED10DA19/840    | 120              | 6          | 4.4      | 800            |              | 4000               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |
|   |           |       | 69146      | LED10DA19/850    | 120              | 6          | 4.4      | 800            |              | 5000               | 80   | 60W                 | 15,000                | Yes      | ★                   | Damp             | White, Omnidirectional |
|   | 11        |       | 29268      | LED11DA19/824    | 120              | 6          | 4.44     | 800            |              | 2400               | 80   | 60W                 | 25,000                | Yes      |                     | Damp             | White, Omnidirectional |
|   |           |       | GU24       | 74357            | LED11DA19827GU24 | 120        | 6        | 4.4            | 800          |                    | 2700 | 80                  | 60W                   | 25,000   | Yes                 |                  | Damp                   |
| A-21  |           |       |            |                  |                  |            |          |                |              |                    |      |                     |                       |          |                     |                  |                        |
|  | MED       | 12    | 76037      | LED12DA19/827    | 120              | 6          | 5.16     | 1100           |              | 2700               | 80   | 75W                 | 15,000                | Yes      | ★                   | Damp             | White, Omni, ES 2.0    |
|   |           |       | 76041      | LED12DA21/830    | 120              | 6          | 5.16     | 1100           |              | 3000               | 80   | 75W                 | 15,000                | Yes      | ★                   | Damp             | White, Omni, ES 2.0    |
|   |           |       | 76045      | LED12DA21/840    | 120              | 6          | 5.16     | 1100           |              | 4000               | 80   | 75W                 | 15,000                | Yes      | ★                   | Damp             | White, Omni, ES 2.0    |
|   |           |       | 76102      | LED12DA21/850    | 120              | 6          | 5.16     | 1100           |              | 5000               | 80   | 75W                 | 15,000                | Yes      | ★                   | Damp             | White, Omni, ES 2.0    |
|   |           |       | 73404      | LED12DA21/850FE  | 120              | 6          | 5.31     | 1100           |              | 5000               | 80   | 75W                 | 25,000                | Yes      |                     | Enclosed         | White, Enclosed, Omni  |
|   |           |       | 73384      | LED12DA21/830FE  | 120              | 6          | 5.31     | 1100           |              | 3000               | 80   | 75W                 | 25,000                | Yes      |                     | Enclosed         | White, Enclosed, Omni  |
|  | 15        |       | 76038      | LED15DA21/827    | 120              | 6          | 5.16     | 1600           |              | 2700               | 80   | 100W                | 15,000                | Yes      | ★                   | Damp             | White, Omni, ES 2.0    |
|   |           |       | 76043      | LED15DA21/830    | 120              | 6          | 5.16     | 1600           |              | 3000               | 80   | 100W                | 15,000                | Yes      | ★                   | Damp             | White, Omni, ES 2.0    |
|   |           |       | 76060      | LED15DA21/840    | 120              | 6          | 5.16     | 1600           |              | 4000               | 80   | 100W                | 15,000                | Yes      | ★                   | Damp             | White, Omni, ES 2.0    |
|   |           |       | 76117      | LED15DA21/850    | 120              | 6          | 5.16     | 1600           |              | 5000               | 80   | 100W                | 15,000                | Yes      | ★                   | Damp             | White, Omni, ES 2.0    |
|   | GU24      | 16    | 92498      | LED16DA21827GU24 | 120              | 6          | 5.43     | 1600           |              | 2700               | 80   | 100W                | 25,000                | Yes      |                     | Damp             | White, Omnidirectional |
|   |           |       | MED        | 73376            | LED16A30/100/827 | 120        | 6        | 5.31           | 360/1400/900 |                    | 2700 | 80                  | 30/70/100             | 25,000   | -                   | ★                | Damp                   |
|   |           |       | 92118      | LED16A30/100/5KB | 120              | 3          | 5.31     | 360/1400/900   |              | 5000               | 80   | 30/70/100           | 25,000                | -        | ★                   | Damp             | White, 3-Way           |
|   |           |       | 73378      | LED22A50/150/827 | 120              | 6          | 5.31     | 700/2155/1600  |              | 2700               | 80   | 50/100/150          | 25,000                | -        | ★                   | Damp             | White, 3-Way           |
|   |           |       | 92120      | LED22A50/150/5KB | 120              | 3          | 5.31     | 700/2155/1600  |              | 5000               | 80   | 50/100/150          | 25,000                | -        | ★                   | Damp             | White, 3-Way           |

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "T/P" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® is a registered U.S. mark

**current**  
powered by GE

<http://products.currentbyge.com>.

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2017 GE.

63563 (Rev 08/18/17)

