

34478 - Ballast Bypass 3ft LED Glass Tubes

LED13BT8/G3/850

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. The existing fixture is wired to bypass the ballast which further reduces energy use and eliminates the need to check ballast compatibility. Additional maintenance savings are realized by removing costs associated with replacing ballasts.
- ☞ Each LED tube is outfitted with a Single-ended In-line fuse
- ☞ 66% longer life than LFL (50 000 vs. 30 000 hours)
- ☞ Easy disposal non-hazardous waste
- ☞ UL Listed
- ☞ Check ballast compatibility at www.gelighting.com/LEDTUBES-ballast-compatibility
- ☞ For In-Line Fuse & Socket Kits please check our Awaken brochure.

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	LED_Bs_G13
Base Type	G13
Dimmable	No
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	No
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Carton
Estimated Energy Cost per Year	1.45
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	146
Initial Lumens-nominal	1900 lm
Color Rendering Index-CRI	80
Color Temperature	5000 K

PRODUCT INFORMATION

Product Code	34478
Description	LED13BT8/G3/850
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168344784
Standard Package GTIN	00043168344784
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168344784
Standard Package GTIN	10043168344781
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	36.0 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Voltage <Nom>	120 V
Rated power (Watts)	13 W