



49767 - GE LFL UltraMax™ Electronic High Efficiency Multivolt Instant Start Ballast

GE259MAXPN/ULTRA UNIV

- ☞ Energy saving high efficiency instant start electronic ballast (> 90%)
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ Active Current Regulation regulates the output to each lamp with individual lamp inverter modules.
- ☞ Anti-Striation Control for better light quality, with no striations.
- ☞ Cold temperature -20F Minimum Starting Temperature

GENERAL CHARACTERISTICS

Ballast Factor	Normal
Ballast Type	High Efficiency Multivolt Instant Start
Case Temperature (Max)	70 °C
Line Voltage Regulation (+/-)	10%
Classification (Regulations)	cUL Listed FCC - CLASS A Non-Consumer UL Class P UL Listed UL Type 1 Outdoor UL Type HL Product is compliant with material restriction requirements of RoHS
Sound Rating	A (20-24 decibels)
Starting Method	Instant start
Product Technology	Linear Fluorescent
Lamp Wiring	Parallel
Power Factor Correction	Active

PRODUCT INFORMATION

Product Code	49767
Description	GE259MAXPN/ULTRA UNIV
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	
Standard Package GTIN	0
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	
UCC	
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168497671
Standard Package GTIN	00043168497671
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	
Alternative Unit Of Measure	CASE
Standard Package Quantity	10
Ean UPC	043168497671
Standard Package GTIN	00000000000000
No Of Items Per Sales Unit	
No Of Items Per Standard Package	10
Sales Unit	Case
UCC	
Alternative Unit Of Measure	CASE
Standard Package Quantity	10
Ean UPC	043168497671
Standard Package GTIN	10043168497678
No Of Items Per Sales Unit	
No Of Items Per Standard Package	10
Sales Unit	Case
UCC	

DIMENSIONS

Weight	1.4 lb
Exit Type	
Remote Mount Distance	18.0 ft

Case Dimensions

Length	9.5in
--------	-------








Width 1.7in
 Height 1.2in

Mounting Dimensions

Mount Length 9.0in
 Mount Width 1.05in
 Mount Slot 0.323in

Lead Color	Qty	Ext	Length (± 1 in.)
Blue	2	Right	46in
White	1	Left	25in
Black	1	Left	25in
Red	1	Right	78in

SAFETY & PERFORMANCE

-  cUL_Listed
-  FCC_CS_NCons
-  UL_Cls_P
-  UL_Listed
-  UL_Type1_Out
-  UL_Type_HL
-  Pro_comp_res_req

CAUTIONS & WARNINGS

Warning


Risk of Electric Shock

Properly ground ballast and fixture.

Turn power off before servicing--see instructions.

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
F40T8	1	120	46	0.39			0.99	1.5	10	0
F40T8	1	277	46	0.18			0.95	1.5	20	0
F40T8	2	120	77	0.66			0.97	1.5	10	0
F96T8/WMP	2	120	98	0.82	0.87	1	0.99	1.7	7	50
F40T8	2	277	76	0.29			0.97	1.5	18	0
F72T8	1	277	44	0.17			0.96	1.5	20	0
F72T8	2	120	79	0.72			0.99	1.5	10	0
F72T8	1	120	44	0.39			0.99	1.5	10	0
F72T8	2	277	78	0.29			0.98	1.5	13	0
F96T8	1	120	57	0.48	0.91	1	1.0	1.5	8	0
F96T8	2	120	108	0.9	0.91	1	1.0	1.5	4	0
F96T8	2	277	104	0.38	0.91	1	0.98	1.5	13	0
F96T8	1	277	57	0.21	0.91	1	0.97	1.5	18	0
F96T8/WM	1	120	55	0.46	0.85	2	1.0	1.7	8	50
F96T8/WM	1	277	55	0.21	0.86	2	0.97	1.5	17	50
F96T8/WM	2	277	100	0.37	0.86	1	0.98	1.7	13	50
F96T8/WM	2	120	103	0.87	0.86	1	1.0	1.7	4	50
F96T8/WMP	1	120	52	0.44	0.87	2	1.0	1.5	8	50
F96T8/WMP	1	277	52	0.2	0.87	2	0.96	1.5	19	50
F96T8/WMP	2	277	94	0.35	0.87	1	0.98	1.5	13	50
F96T849W	1	120	48	0.4	0.87	2	1.0	1.7	10	50
F96T849W	1	277	48	0.18	0.87	2	0.96	1.7	20	50
F96T849W	2	120	88	0.75	0.87	1	0.99	1.7	10	50
F96T849W	2	277	85	0.31	0.88	1	0.98	1.5	15	50



Apr 19, 2021 7:51:17 PM | For additional information, visit <https://products.gecurrent.com/>