



66955 - LET75W277BF

GELT75A27712RBF 277

Previous SKU: 901075278

### GENERAL CHARACTERISTICS

Enclosure Type	Plastic
Ambient Temp [Max]	50 °C
Ambient Temp [Min]	0 °C
Storage Temperature	min(-10), max(70) °C
Color	Black
Line Voltage Regulation (+/-)	120-277
Product Technology	Halogen
Rated Life Hours-nominal	0 h
CC/CVValue	Voltage line depended
Output Power (W)	75 W
Output Current (A)	6.25 A
Output Voltage[Min]	11.2 V
Output Voltage[Max]	11.8 V
Output Voltage[Nom]	120 V
Output Voltage Range (dimming) (V)	0-11.8 V
Total Harmonic Distortion (THD)	15 %

### PRODUCT INFORMATION

Product Code	66955
Description	GELT75A27712RBF 277
Alternative Unit Of Measure	CASE
Standard Package Quantity	0
Ean UPC	043168669559
Standard Package GTIN	10043168669556
No Of Items Per Sales Unit	
No Of Items Per Standard Package	0
Sales Unit	Case
UCC	043168669559
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168669559
Standard Package GTIN	00043168669559
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168669559

### DIMENSIONS

Remote Mount Distance	50.8 m
Width	88.3 mm
Height	36.5 mm
Weight	29.1 mm

Lead Color Qty Exit Length (± 1 In.)

### ELECTRICAL CHARACTERISTICS

Power Factor %	Passive
Output Current Frequency-Hertz	33 kHz
Outrush Current (Milliamperes)	33 kHz
Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.35 A
Input Voltage Range[Min] (V)	0.35 A
Input Voltage Range[Max]	252 V
Input Current Range (Amperes)	305
Input voltage Range	V V
Rated power (Watts)	0 W