

71628 - GE Ecolux® Watt-Miser® Starcoat® T5

F54T5/835/WM/ECO

- ☞ Saves energy compared to standard wattage lamps
- ☞ Passes TCLP, which can lower disposal costs.

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	2.5 mg
Mercury-Picogram per mean lm hr	18.1
Rated Life Rapid Start - Hrs	30000 h @ 3 h 36000 h @ 12 h
Starting Temp (MIN) C-degrees	-20 °C
Bulb Material	Soda lime
Rated Life Hours-nominal	0 h
Primary Application	Energy Saving
Product Technology	Linear Fluorescent
Base	G5

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	4600 lm
Nominal Initial Lumen per Watt	0
Initial Lumens-nominal	0 lm
Color Rendering Index-CRI	0

PRODUCT INFORMATION


Product Code	71628
Description	F54T5/835/WM/ECO
Alternative Unit Of Measure	CASE
Standard Package Quantity	40
Ean UPC	043168716284
Standard Package GTIN	10043168716281
No Of Items Per Sales Unit	
No Of Items Per Standard Package	40
Sales Unit	Case
UCC	043168716284
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168716284
Standard Package GTIN	00043168716284
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	

DIMENSIONS

Bulb Diameter (DIA) <Max>	0.67 in
Diameter	0.62 in
Face to End of Opposing Pin (B) <Max>	45.52 in
Face to End of Opposing Pin (B) <Min>	45.42 in
Nominal Length	45.2 in

ELECTRICAL CHARACTERISTICS

Scotopic/Photopic Ratio	1.5
Current Crest Factor (MAX)	1.7
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Rated power (Watts)	0 W



Mar 11, 2021 7:55:11 PM | For additional information, visit <https://products.gecurrent.com/>



Lamp Contains Mercury

Manage in Accord with Disposal Laws

See : www.lamprecycle.org or 1-800-327-0097