

72113 - GE Ecolux® Mod-U-line® Starcoat® T8

F32T8SPX41U6/ECO

Passes TCLP, which can lower disposal costs.

PRODUCT PHOTO

CAUTIONS & WARNINGS

Warning

Risk of Electric Shock Turn power off before inspection

installation or removal.

Caution

GENERAL CHARACTERISTICS

Base Description Base Face to Top of Lamp Max Base Type Mercury Content Mercury-Picogrm per mean Im hr Rated Life Rapid Start - Hrs Starting Temp (MIN) C-degrees Bulb Material Rated Life Hours-nominal Primary Application Product Technology Base Bulb Shape

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal Nominal Initial Lumen per Watt Initial Lumens-nominal Color Rendering Index-CRI Color Temperature

PRODUCT INFORMATION

Product Code Description Alternative Unit Of Measure Standard Package Quantity Ean UPC Standard Package GTIN No Of Items Per Sales Unit No Of Items Per Standard Package Sales Unit UCC Alternative Unit Of Measure Standard Package Quantity Ean UPC Standard Package GTIN No Of Items Per Sales Unit No Of Items Per Standard Package Sales Unit UCC

DIMENSIONS

Diameter	1.0 in
Bulb Diameter in Bend <max></max>	1.13 in
Bulb Diameter in Bend <min></min>	0.89 in
Bulb Diameter in Legs <max></max>	1.1 in
Bulb Diameter in Legs <min></min>	0.94 in
Lamplegs Center-Center Length	6.0 in
Nominal Length	22.5 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Rated power (Watts)	32 W

Medium Bi-Pin (G13) 22.250 Pin/Plug-In 3.75 mg 76.1 20000 h @ 3 h 10 °C Soda lime 20000 h Full Wattage Linear Fluorescent G13 T8

2505 lm 87.5 2800 lm 82 4100 K


1


Each


Lamp may shatter and cause injury if broken

Wear safety glasses and gloves when handling lamp.

Do not use excessive force when installing lamp.







Sep 8, 2020 5:20:07 PM | For additional information, visit https://products.gecurrent.com/



Lamp Contains Mercury Manage in Accord with Disposal Laws See : www.lamprecycle.org or 1-800-327-0097