



97597 - GE Ecolux® Blax® T4 - Facilities. Retail Display. Hospitality.
Office. Restaurant. Warehouse
F13DBX/841/EC04P

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	17000 h
Starting Temp (MIN) C-degrees	0 °C
Mercury-Picogram per mean lm hr	198.7
Primary Application	Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Lamp Count	1
Base	G24q-1
Bulb Shape	T4

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	755 lm
Nominal Initial Lumen per Watt	69
Color Rendering Index-CRI	82

PRODUCT INFORMATION

Product Code	97597
Description	F13DBX/841/EC04P
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168975971
Standard Package GTIN	00043168975971
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168975971
Alternative Unit Of Measure	CASE
Standard Package Quantity	50
Ean UPC	043168975971
Standard Package GTIN	30043168975972
No Of Items Per Sales Unit	
No Of Items Per Standard Package	50
Sales Unit	Case
UCC	043168975971

DIMENSIONS

Base Face to Top of Lamp	4.4 in
Nominal Length	5.0 in
Bulb Max Overall Length-MOL	5.2 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	60 W
Current Crest Factor (MAX)	5.25
Supply Current Freq nominal Hz	60 Hz
Rated power (Watts)	13 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).



Lamp Contains Mercury

Manage in Accord with Disposal Laws

See : www.lamprecycle.org or 1-800-327-0097