



31068 - GE Protected ConstantColor® CMH® Ceramic Metal Halide ED17

CMH150CU942MED/O

GENERAL CHARACTERISTICS

Base Description	Medium Screw
Base Temp C-degrees (MAX)	190 °C
Base Type	Screw-In
Bulb Temperature C-degree(MAX)	400 °C
Lamp Enclosure Type (LET)	Open or enclosed fixtures
Mercury-Picogram per mean lm hr	72.3
Rated Life Hours-nominal	15000 h
Bulb Finishes and Colors	Coated
Mercury Content EMEA ONLY	19
Bulb Material	Hard glass
Product Technology	High Intensity Discharge
Lamp Count	1
Life in Years	3.73
Requested Structure	Sleeve
Base	E26
Bulb Shape	ED17

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	8300 lm
Nominal Lumens per Watt	73 lm
Initial Lumens-nominal	11000 lm
Color Rendering Index-CRI	90
Color Temperature	4200 K

PRODUCT INFORMATION

Product Code	31068
Description	CMH150CU942MED/O
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168310680
Standard Package GTIN	00043168310680
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168310680
Alternative Unit Of Measure	CASE
Standard Package Quantity	6
Ean UPC	043168310680
Standard Package GTIN	10043168310687
No Of Items Per Sales Unit	6
No Of Items Per Standard Package	6
Sales Unit	Case
UCC	043168310680

DIMENSIONS

Diameter	2.13 in
Light Center Length Millimeter	3.38 in
Nominal Length	5.43 in

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Hot Restart Time to 90%MAX	15 min
Estimated Energy Cost per Year	66.24
Input Voltage [nom]	120 W
Rated power (Watts)	150 W

CAUTIONS & WARNINGS

WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

Caution

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use excessive force when installing lamp.

Do not use lamp if outer glass is scratched or broken.

Warning

A damaged lamp emits UV radiation which may cause eye/skin injury

Turn power off if glass bulb is broken. Remove and dispose of lamp.

Risk of Burn

Allow lamp to cool before handling.

Do not turn on lamp until fully installed.

Risk of Electric Shock

Do not use where directly exposed to water or outdoors without an enclosed fixture.

Turn power off before inspection

installation or removal.

Risk of Fire

Keep combustible materials away from lamp.

Use in fixture rated for this product.

Unexpected lamp rupture may cause injury, fire, or property damage

Do not exceed rated voltage.

Do not store flammable materials near/below S-rated lamp in open fixture

Do not turn on lamp until fully installed.

Do not use beyond rated life.

Do not use lamp if outer glass is scratched or broken.

Do not use where directl

NOTES

Rated life based on 11 hours per start