

Presented By: iLightDepot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com


Customer Name:
Project Name:
Fixture Type:



GE
Lighting

97587 - F13DBX23/830/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

NOTES

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	GX23-2
Rated Life	10000.0 hrs
Starting Temperature (MIN)	-4.0 °C
Cathode Resistance	10.5 Ohm
LEED-EB MR Credit	584 picograms Hg per mean lumen hour
Additional Info	TCLP compliant
Primary Application	Standard;Facilities;Retail Display;Hospitality;Office;Restaurant;Warehouse

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	810.0
Mean Lumens	685.0
Nominal Initial Lumens per Watt	62
Color Temperature	3000.0 K
Color Rendering Index (CRI)	82.0

ELECTRICAL CHARACTERISTICS

Wattage	13.0
Open Circuit Voltage Across Starter (MIN)	198.0 V
Lamp Current	0.285 A
Current Crest Factor (MAX)	1.7
Supply Current Frequency	60.0 Hz

DIMENSIONS

Maximum Overall Length (MOL)	4.8400 in(122.9 mm)
Nominal Length	4.700 in(119.4 mm)
Base Face to Top of Lamp	3.900 in(99.1 mm)

PRODUCT INFORMATION

Product Code	97587
Description	F13DBX23/830/ECO
Standard Package	BUNDLE
Standard Package GTIN	
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168975872