Presented By: iLightDepot Contact Phone: 513-272-0800

Contact E-mail: sales@ilightdepot.com

Customer Name: Project Name: Fixture Type:



GE Lighting

97632 - F32TBX/841/A/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse









CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

GENERAL CHARACTERISTICS

Lamp Type Compact Fluorescent - Plug-

| In | T4 | Base | GX24q-3 | Rated Life | 17000.0 | hrs | Starting Temperature (MIN) | 0.0 | K | Cathode Resistance | 2.7 | Ohm

LEED-EB MR Credit 87 picograms Hg per mean

lumen hour

Rated Life (rapid start) @ Time 17000.0 @ 3.0/20000.0 @

12.0 h

Additional Info Dimmable with appropriate dimming ballast./End of

Life Protection (EOL)/TCLP

compliant

Primary Application Facilities; Retail

Display; Hospitality; Office; Restaurant; Wa

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 2400.0
Mean Lumens 2040.0
Nominal Initial Lumens per Watt
Color Temperature 4100.0 K
Color Rendering Index (CRI) 82.0

ELECTRICAL CHARACTERISTICS

 Wattage
 32.0

 Voltage
 120.0

 Current (max)
 5.25 A

 Open Circuit Voltage (after
 265.0 V

preheating) (MAX)

Open Circuit Voltage (MIN)

Lamp Current

Preheat Voltage (MIN)

Current Crest Factor (MAX)

Supply Current Frequency

515.0 V

4.25 V

1.7

Supply Current Frequency

20000.0 Hz

apply culterit i requestoy 2000

DIMENSIONS

Maximum Overall Length 5.5000 in(139.7 mm)

(MOL)

Nominal Length 5.500 in(139.7 mm)

Base Face to Top of Lamp 4.9 cm

PRODUCT INFORMATION

Product Code 97632

Description F32TBX/841/A/ECO ANSI Code 60901-IEC-7432-2

Standard Package Case

Standard Package GTIN 10043168976326

Standard Package Quantity
Sales Unit
No Of Items Per Sales Unit
No Of Items Per Standard

10

Package

UPC 043168976329

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Based on 60Hz reference circuit
- Fluorescent lamp lumens decline during life