

Presented By: iLightDepot/GE Lighting Depot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com

Customer Name:
Project Name:
Fixture Type:





GE
Lighting

29676 - GE-332-MVPS-H

GE LFL UltraStart® Electronic Program / Rapid Start Ballast

- A new generation of ultra-efficient Programmed Start ballasts (> 90% efficiency).
- Extends lamp life in frequently switched applications (> 100,000 on/off cycles)
- Starting time visually the same as instant start
- Multi-Voltage Technology handles voltage from 120 to 277V
- Parallel lamp operation means system maintenance is easier to manage
- Anti-striation circuitry reduces striations with energy saving lamps



GENERAL CHARACTERISTICS

Application	3 F32T8 120V-277V High Light
	1.15 BF<10% THD UltraStart
Category	Linear Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	High (1.18)
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Additional Info	Auto-restart/Thermally protected

PRODUCT INFORMATION

Product Code	29676
Description	GE-332-MVPS-H
Standard Package	Case
Standard Package GTIN	10043168296769
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168296762

DIMENSIONS

Case dimensions			
Length (L)	9.5 in(241.30 mm)		
Width (W)	1.7 in(43.18 mm)		
Height (H)	1.2 in(29.97 mm)		
Mounting dimensions			
Bracket Length (BL)	NaN in(NaN mm)		
Mount Length (M)	8.9 in(225.81 mm)		
Mount Width (X or F)	1.1 in(28.70 mm)		
Mount Slots (MS)	0.3 in(7.92 mm)		
Weight	2.4 lb		
Exit Type	Side		
Remote Mounting Distance	18.0 ft		
Remote Mounting Wire Gauge	18.0 AWG		
Lead lengths	Qty	Exit	Length (± 1 in.)
White	1	Left	25 in (NaNm)
Black	1	Left	25.0 (635mm)
Yellow	2	Right	47.0 (1194mm)
Blue	2	Right	33.0 (838mm)
Red	2	Right	33.0 (838mm)
Red/White	2	Right	33.0 (838mm)

ELECTRICAL CHARACTERISTICS

Supply Current Frequency (MIN)	50.0 Hz
Supply Current Frequency	60.0 Hz

SAFETY & PERFORMANCE

- ANSI - C62.41
- cUL Listed
- FCC - CLASS A Non-Consumer
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type HL
- RoHS Compliant
- NEMA Premium®
- High Temperature Rated: Suitable for high temperature applications
- 70C max case temp 5 yr warranty or 90C max case temp 3 yr warranty

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor THD% (<=)	Min. Starting Temp (°F/°C)
F32T8/WM	2	120	77	0.64 A			98	1.7 10.0	50.0 °F / NaN

F32T8/WM	2	277	76	0.3 A	1.26	1.66	95	1.7	10.0	50.0 °F / NaN
F32T8/WM	3	120	102	0.88 A	1.13	1.11	99	1.7	10.0	50.0 °F / NaN
F32T8/WM	3	277	100	0.39 A	1.14	1.14	96	1.7	10.0	50.0 °F / NaN
F32T8/25W	2	120					98	1.7	10.0	50.0 °F / NaN
F32T8/25W	2	277					98	1.7	10.0	50.0 °F / NaN
F32T8/25W	3	120	87		1.09	1.25	98	1.7	10.0	50.0 °F / NaN
F32T8/25W	3	277	86		1.09	1.27	98	1.7	10.0	50.0 °F / NaN
F32T8	2	120	82	0.7 A	1.28	1.56	98	1.7	10.0	0.0 °F / NaN
F32T8	2	277	82	0.32 A			94	1.7	10.0	0.0 °F / NaN
F32T8	3	120	110	0.95 A	1.15	1.05	98	1.7	10.0	0.0 °F / NaN
F32T8	3	277	108	0.41 A	1.15	1.06	96	1.7	10.0	0.0 °F / NaN
F28T8	2	120	68	0.58 A	1.23	1.81	98	1.7	10.0	50.0 °F / NaN
F28T8	2	277	69	0.27 A	1.23	1.78	94	1.7	10.0	50.0 °F / NaN
F28T8	3	120	92	0.79 A	1.09	1.18	99	1.7	10.0	50.0 °F / NaN
F28T8	3	277	91	0.35 A	1.10	1.21	96	1.7	10.0	50.0 °F / NaN
F25T8	2	120	65	0.56 A	1.25	1.92	98	1.7	10.0	0.0 °F / NaN
F25T8	2	277	64	0.26 A			93	1.7	10.0	0.0 °F / NaN
F25T8	3	120	86	0.74 A	1.14	1.33	98	1.7	10.0	0.0 °F / NaN
F25T8	3	277	85	0.33 A	1.14	1.34	96	1.7	10.0	0.0 °F / NaN
F17T8	2	120	45	0.38 A	1.25	2.78	98	1.7	10.0	0.0 °F / NaN
F17T8	2	277	45	0.19 A			90	1.7	10.0	0.0 °F / NaN
F17T8	3	120	59	0.52 A	1.13	1.92	98	1.7	10.0	0.0 °F / NaN
F17T8	3	277	59	0.24 A	1.13	1.92	93	1.7	10.0	0.0 °F / NaN

CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Properly ground ballast and fixture.
 - Turn power off before servicing--see instructions.

NOTES

- Instant Start Rated Lamp

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.