

Presented By: iLightDepot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com

Customer Name:
Project Name:
Fixture Type:





GE
Lighting

75954 - GE132-MVPS-H

GE LFL UltraStart® Electronic Program / Rapid Start Ballast

- A new generation of ultra-efficient Programmed Start ballasts (> 90% efficiency).
- Extends lamp life in frequently switched applications (> 100,000 on/off cycles)
- Starting time visually the same as instant start
- Multi-Voltage Technology handles voltage from 120 to 277V
- Anti-striation circuitry reduces striations with energy saving lamps



GENERAL CHARACTERISTICS

Application	1 F32T8 120V-277V High Light
	1.18 BF<10% THD UltraStart
Category	Linear Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	High (1.18)
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Additional Info	Auto-restart/Thermally protected

PRODUCT INFORMATION

Product Code	75954
Description	GE132-MVPS-H
Standard Package	Case
Standard Package GTIN	10043168759547
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168759540

DIMENSIONS

Case dimensions			
Length (L)	9.5 in(241.30 mm)		
Width (W)	1.7 in(43.18 mm)		
Height (H)	1.2 in(29.97 mm)		
Mounting dimensions			
Bracket Length (BL)	NaN in(NaN mm)		
Mount Length (M)	8.9 in(225.81 mm)		
Mount Width (X or F)	1.1 in(28.70 mm)		
Mount Slots (MS)	0.3 in(7.92 mm)		
Weight	1.4 lb		
Exit Type	Side		
Remote Mounting Distance	18.0 ft		
Remote Mounting Wire Gauge	18.0 AWG		
Lead lengths	Qty	Exit	Length (± 1 in.)
White	1	Left	25.0 (635mm)
Black	1	Left	25.0 (635mm)
Yellow	2	Right	48.0 (1219mm)
Blue	2	Right	33.0 (838mm)

ELECTRICAL CHARACTERISTICS

Supply Current Frequency	60.0 Hz
--------------------------	---------

SAFETY & PERFORMANCE

- ANSI - C62.41
- cUL Listed
- FCC - CLASS A Non-Consumer
- NRCan
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type HL
- RoHs Compliant
- NEMA Premium®
- High Temperature Rated: Suitable for high temperature applications
- 70C max case temp 5 yr warranty or 90C max case temp 3 yr warranty

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor	THD% (<=)	Min. Starting Temp (°F/°C)
FE15T8	1	120	17	0.15 A	1.05	6.18	99	1.7	10.0	0.0 °F / NaN
FE15T8	1	277	18	0.08 A	1.05	5.83	88	1.7	10.0	0.0 °F / NaN
F40T8	1	120	48	0.42 A	1.18	2.46	99	1.7	10.0	0.0 °F / NaN
F40T8	1	277	47	0.18 A	1.18	2.51	98	1.7	10.0	0.0 °F / NaN

F32T8/WM	1	120	36	0.32 A	1.16	3.22	99	1.7	10.0	50.0 °F / NaN
F32T8/WM	1	277	36	0.14 A	1.16	3.22	96	1.7	10.0	50.0 °F / NaN
F32T8/25W	1	120	31	0.27 A	1.15	3.71	99	1.7	10.0	50.0 °F / NaN
F32T8/25W	1	277	31	0.12 A	1.15	3.71	95	1.7	10.0	50.0 °F / NaN
F32T8	1	120	39	0.35 A	1.18	3.03	98	1.7	10.0	0.0 °F / NaN
F32T8	1	277	39	0.15 A	1.18	3.03	97	1.7	10.0	0.0 °F / NaN
F28T8	1	120	33	0.29 A	1.16	3.52	99	1.7	10.0	50.0 °F / NaN
F28T8	1	277	33	0.13 A	1.16	3.52	96	1.7	10.0	50.0 °F / NaN
F25T8/WM	1	120	26	0.23 A	1.16	4.46	99	1.7	10.0	50.0 °F / NaN
F25T8/WM	1	277	27	0.1 A	1.16	4.30	94	1.7	10.0	50.0 °F / NaN
F25T8	1	120	30	0.27 A	1.17	3.90	99	1.7	10.0	0.0 °F / NaN
F25T8	1	277	30	0.12 A	1.17	3.90	95	1.7	10.0	0.0 °F / NaN
F25T12	1	120	33	0.29 A	1.25	3.79	99	1.7	10.0	0.0 °F / NaN
F25T12	1	277	33	0.13 A	1.25	3.79	96	1.7	10.0	0.0 °F / NaN
F17T8/WM	1	120	19	0.17 A	1.18	6.21	99	1.7	10.0	50.0 °F / NaN
F17T8/WM	1	277	19	0.08 A	1.18	6.21	89	1.7	10.0	50.0 °F / NaN
F17T8	1	120	21	0.19 A	1.19	5.67	99	1.7	10.0	0.0 °F / NaN
F17T8	1	277	22	0.09 A	1.19	5.41	91	1.7	10.0	0.0 °F / NaN

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.