

Presented By: iLightDepot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com


Customer Name:
Project Name:
Fixture Type:



75952 - GE132-MVPS-L

GE LFL UltraStart® Electronic Program / Rapid Start Ballast

- A new generation of ultra-efficient Programmed Start ballasts (> 90% efficiency).
- Extends lamp life in frequently switched applications (> 100,000 on/off cycles)
- Multi-Voltage Technology handles voltage from 120 to 277V
- Starting time visually the same as instant start
- Anti-striation circuitry reduces striations with energy saving lamps



GENERAL CHARACTERISTICS

Application	1 F32T8 120V-277V Low Watts .71 BF <10% THD UltraStart
Category	Linear Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Low-PS (.71)
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Anti-striation control/Thermally protected/Universal voltage Standard
Primary Application	Standard

PRODUCT INFORMATION

Product Code	75952
Description	GE132-MVPS-L
Standard Package	Case
Standard Package GTIN	10043168759523
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168759526

DIMENSIONS

Case dimensions			
Length (L)	9.5 in(241.30 mm)		
Width (W)	1.7 in(43.18 mm)		
Height (H)	1.2 in(29.97 mm)		
Mounting dimensions			
Bracket Length (BL)	NaN in(NaN mm)		
Mount Length (M)	8.9 in(225.81 mm)		
Mount Width (X or F)	1.1 in(28.70 mm)		
Mount Slots (MS)	0.3 in(7.92 mm)		
Weight	1.65 lb		
Remote Mounting Distance	18.0 ft		
Remote Mounting Wire Gauge	18.0 AWG		
Lead lengths	Qty	Exit	Length (± 1 in.)
Black	1	Left	25.0 (635mm)
White	1	Left	25.0 (635mm)
Blue	2	Right	33.0 (838mm)
Yellow	2	Right	48.0 (1219mm)

ELECTRICAL CHARACTERISTICS

Supply Current Frequency (MIN)	50.0 Hz/60.0 Hz
--------------------------------	-----------------

SAFETY & PERFORMANCE

- ANSI - C62.41
- cUL Listed
- FCC - CLASS A Non-Consumer
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type HL
- RoHs Compliant
- NEMA Premium®

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor	THD% (<=)	Min. Starting Temp (°F/°C)
FE15T8	1	120	12	0.1 A	0.66	5.50	99	1.7	10.0	0.0 °F / NaN
FE15T8	1	277	13	0.1 A	0.66	5.08	86	1.7	10.0	0.0 °F / NaN
F40T8	1	120	29	0.25 A	0.71	2.45	99	1.7	10.0	0.0 °F / NaN
F40T8	1	277	29	0.11 A	0.71	2.45	97	1.7	10.0	0.0 °F / NaN

F32T8/WM	1	120	23	0.2 A	0.71	3.09	99	1.7	10.0	50.0 °F / NaN
F32T8/WM	1	277	23	0.09 A	0.71	3.09	95	1.7	10.0	50.0 °F / NaN
F32T8/25W	1	120	20	0.18 A	0.71	3.55	99	1.7	10.0	50.0 °F / NaN
F32T8/25W	1	277	21	0.08 A	0.71	3.38	94	1.7	10.0	50.0 °F / NaN
F32T8	1	120	25	0.22 A	0.72	2.88	99	1.7	10.0	0.0 °F / NaN
F32T8	1	277	25	0.1 A	0.72	2.88	96	1.7	10.0	0.0 °F / NaN
F28T8	1	120	22	0.19 A	0.71	3.23	99	1.7	10.0	50.0 °F / NaN
F28T8	1	277	22	0.09 A	0.71	3.23	94	1.7	10.0	50.0 °F / NaN
F25T8/WM	1	120	17	0.15 A	0.71	4.18	99	1.7	10.0	50.0 °F / NaN
F25T8/WM	1	277	18	0.07 A	0.71	3.94	92	1.7	10.0	50.0 °F / NaN
F25T8	1	120	19	0.17 A	0.73	3.84	99	1.7	10.0	0.0 °F / NaN
F25T8	1	277	20	0.08 A	0.73	3.65	93	1.7	10.0	0.0 °F / NaN
F25T12	1	120	20	0.18 A	0.72	3.60	99	1.7	10.0	0.0 °F / NaN
F25T12	1	277	21	0.08 A	0.72	3.43	94	1.7	10.0	0.0 °F / NaN
F17T8/WM	1	120	13	0.11 A	0.74	5.69	99	1.7	10.0	50.0 °F / NaN
F17T8/WM	1	277	13	0.06 A	0.74	5.69	87	1.7	10.0	50.0 °F / NaN
F17T8	1	120	14	0.12 A	0.75	5.36	99	1.7	10.0	0.0 °F / NaN
F17T8	1	277	15	0.06 A	0.75	5.00	89	1.7	10.0	0.0 °F / NaN

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.