

Presented By: iLightDepot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com

Customer Name:
Project Name:
Fixture Type:





GE
Lighting

75953 - GE132-MVPS-N

GE LFL UltraStart® Electronic Program / Rapid Start Ballast

- < 10% THD, > 99% power factor
- A new generation of ultra-efficient Programmed Start ballasts (> 90% efficiency).
- Anti-striation circuitry reduces striations with energy saving lamps
- Extends lamp life in frequently switched applications (> 100,000 on/off cycles)
- Multi-Voltage Technology handles voltage from 120 to 277V
- Starting time visually the same as instant start



GENERAL CHARACTERISTICS

Application	1 F32T8 120V-277V Normal Light .88 BF<10% THD UltraStart
Category	Linear Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Anti-striation control/Thermally protected/Universal voltage Standard
Primary Application	Standard

PRODUCT INFORMATION

Product Code	75953
Description	GE132-MVPS-N
Standard Package	Case
Standard Package GTIN	10043168759530
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168759533

DIMENSIONS

Case dimensions			
Length (L)	9.5 in(241.30 mm)		
Width (W)	1.7 in(43.18 mm)		
Height (H)	1.2 in(29.97 mm)		
Mounting dimensions			
Bracket Length (BL)	NaN in(NaN mm)		
Mount Length (M)	8.9 in(225.81 mm)		
Mount Width (X or F)	1.1 in(28.70 mm)		
Mount Slots (MS)	0.3 in(7.92 mm)		
Weight	1.65 lb		
Exit Type	Side		
Remote Mounting Distance	18.0 ft		
Remote Mounting Wire Gauge	18.0 AWG		
Lead lengths	Qty	Exit	Length (± 1 in.)
White	1	Left	25.0 (635mm)
Black	1	Left	25.0 (635mm)
Yellow	2	Right	48.0 (1219mm)
Red	2	Right	33.0 (838mm)
Blue	2	Right	33.0 (838mm)

ELECTRICAL CHARACTERISTICS

Supply Current Frequency (MIN)	50.0 Hz/60.0 Hz
Supply Current Frequency	50.0 Hz

SAFETY & PERFORMANCE

- ANSI - C62.41
- cUL Listed
- FCC - CLASS A Non-Consumer
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type HL
- RoHs Compliant
- NEMA Premium®

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor THD% (<=)	Min. Starting Temp (°F/°C)
FE15T8	1	120	14	0.12 A	0.80	5.71	99	1.7 10.0	0.0 °F / NaN
FE15T8	1	277	15	0.06 A	0.80	5.33	83	1.7 10.0	0.0 °F / NaN

For additional information, visit www.gelighting.com

F40T8	1	120	35	0.31 A	0.88	2.51	99	1.7	10.0	0.0 °F / NaN
F40T8	1	277	35	0.01 A	0.88	2.51	96	1.7	10.0	0.0 °F / NaN
F32T8/WM	1	120	28	0.24 A	0.87	3.11	99	1.7	10.0	50.0 °F / NaN
F32T8/WM	1	277	28	0.11 A	0.87	3.11	94	1.7	10.0	50.0 °F / NaN
F32T8/25W	1	120	24	0.21 A	0.86	3.58	99	1.7	10.0	50.0 °F / NaN
F32T8/25W	1	277	24	0.1 A	0.86	3.58	93	1.7	10.0	50.0 °F / NaN
F32T8	1	120	30	0.26 A	0.89	2.97	99	1.7	10.0	0.0 °F / NaN
F32T8	1	277	30	0.12 A	0.89	2.97	95	1.7	10.0	0.0 °F / NaN
F28T8	1	120	26	0.22 A	0.87	3.35	99	1.7	10.0	50.0 °F / NaN
F28T8	1	277	26	0.1 A	0.87	3.35	93	1.7	10.0	50.0 °F / NaN
F25T8/WM	1	120	20	0.18 A	0.88	4.40	99	1.7	10.0	50.0 °F / NaN
F25T8/WM	1	277	21	0.08 A	0.88	4.19	90	1.7	10.0	50.0 °F / NaN
F25T8	1	120	24	0.2 A	0.89	3.71	99	1.7	10.0	0.0 °F / NaN
F25T8	1	277	24	0.09 A	0.89	3.71	92	1.7	10.0	0.0 °F / NaN
F25T12	1	120	25	0.21 A	0.89	3.56	99	1.7	10.0	0.0 °F / NaN
F25T12	1	277	25	0.1 A	0.89	3.56	93	1.7	10.0	0.0 °F / NaN
F17T8/WM	1	120	15	0.13 A	0.90	6.00	99	1.7	10.0	50.0 °F / NaN
F17T8/WM	1	277	15	0.07 A	0.90	6.00	85	1.7	10.0	50.0 °F / NaN
F17T8	1	120	17	0.15 A	0.91	5.35	99	1.7	10.0	0.0 °F / NaN
F17T8	1	277	18	0.07 A	0.91	5.06	87	1.7	10.0	0.0 °F / NaN

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.