

Presented By: iLightDepot/GELightingDepot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com

Customer Name:
Project Name:
Fixture Type:



**GE
Lighting**

75384 - GE332MVPS-H-V03

GE LFL UltraStart™ T8 100-3% 0-10V Dimming Electronic Dimming Ballast

- High Efficiency 100-3% 0-10V Programmed Start Dimming
- Multi-Voltage Technology handles voltage from 120 to 277V
- Cathode Cutout technology from 100-80%
- Parallel Lamp Operation - reliable deep dimming performance
- NEMA LL-9 Compliant - GE programmed start life & warranty ratings
- Anti-Striation Control for use with F32T8, F32T8/WM, F28T8 and 3 ft. and 2 ft. T8 Lamps
- Fast Starting Time
- UL Type CC Rating provides protection against arcing in electrical devices.
- UL 55C Ambient Rating - HighTemperature Protection Circuit
- Compatible with Class 1 or Class 2 LV 0-10VDC controllers



GENERAL CHARACTERISTICS

Application 3 - F32T8 120-277V "H" 1.18 BF UltraStart 0-10V Dimming 100-3%
Category Linear Fluorescent
Ballast Type Electronic - Dimming
Starting Method Rapid start
Lamp Wiring Parallel
Line Voltage Regulation (+/-) 10.0 %
Ambient Temperature (MAX) 40.0 °C(4 °C)
Ballast Factor High (1.18)
Sound Rating A (20-24 decibels)
Additional Info Anti-striation control/Parallel Lamp Operation/No PCBs

PRODUCT INFORMATION

Product Code 75384
Description GE332MVPS-H-V03
Standard Package Case
Standard Package GTIN 10043168753842
Standard Package Quantity 10
Sales Unit Standard Pack
No Of Items Per Sales Unit 1
No Of Items Per Standard 10
Package
UPC 043168753845

DIMENSIONS

Case dimensions
Length (L) 9.5 in(241.30 mm)
Width (W) 1.7 in(43.18 mm)
Height (H) 1.2 in(29.97 mm)
Mounting dimensions
Bracket Length (BL) NaN in(NaN mm)
Mount Length (M) 8.9 in(225.81 mm)
Mount Width (X or F) 1.1 in(28.70 mm)
Mount Slots (MS) 0.3 in(7.92 mm)
Weight 1.65 lb
Lead lengths Qty

Black	1	Left	25 (635mm)
White	1	Left	25 (635mm)
Blue	2	Right	33 (838mm)
Red	2	Right	33 (838mm)
Red/White	2	Right	33 (838mm)
Yellow	2	Right	48 (1219mm)

SAFETY & PERFORMANCE

- Meets ANSI Standard C62.41-1991
- FCC Part 18 (Class A) for EMI and RFI Non-Consumer Limits
- UL Class P
- UL Type 1 Outdoor
- UL Type HL
- UL Type CC
- RoHs Compliant
- No PCB's
- Complies with ANSI C82.11 Annex A Specification for Low Voltage Control Interface for Controllable Ballasts
- Class 1 or 2 Circuit 10V, 0.5mA

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor	THD% (<=)	Min. Starting Temp (°F/°C)
F32T8/WM	2	120	81	0.67 A	1.26	1.56	98	1.7	10.0	60.0 °F / NaN
F32T8/WM	2	277	80	0.3 A	1.26	1.58	90	1.7	10.0	60.0 °F / NaN
F32T8/WM	3	120	106	0.86 A	1.16	1.09	98	1.7	10.0	60.0 °F / NaN
F32T8/WM	3	277	104	0.38 A	1.16	1.12	98	1.7	10.0	60.0 °F / NaN
F32T8/WM	3	120	17	0.14 A	0.03	0.18	90	1.7	15.0	60.0 °F / NaN

F32T8/WM	3	277	17	0.07	A	0.03	0.18	90	1.7	20.0	60.0 °F / NaN
F32T8/WM	2	120	14	0.12	A	0.05	0.36	80	1.7	15.0	60.0 °F / NaN
F32T8/WM	2	277	14	0.06	A	0.05	0.36	89	1.7	20.0	60.0 °F / NaN
F32T8	2	120	87	0.73	A	1.26	1.45	98	1.7	10.0	60.0 °F / NaN
F32T8	2	277	84	0.31	A	1.26	1.50	98	1.7	10.0	60.0 °F / NaN
F32T8	3	120	116	0.97	A	1.18	1.02	98	1.7	10.0	60.0 °F / NaN
F32T8	3	277	113	0.41	A	1.18	1.04	98	1.7	10.0	60.0 °F / NaN
F32T8	3	120	17	0.14	A	0.03	0.18	90	1.7	15.0	60.0 °F / NaN
F32T8	3	277	17	0.07	A	0.03	0.18	90	1.7	20.0	60.0 °F / NaN
F32T8	2	120	14	0.12	A	0.05	0.36	80	1.7	15.0	60.0 °F / NaN
F32T8	2	277	14	0.06	A	0.05	0.36	80	1.7	20.0	60.0 °F / NaN
F28T8	2	120	73	0.62	A	1.25	1.71	98	1.7	10.0	60.0 °F / NaN
F28T8	2	277	71	0.26	A	1.25	1.76	98	1.7	10.0	60.0 °F / NaN
F28T8	3	120	93	0.73	A	1.15	1.24	98	1.7	10.0	60.0 °F / NaN
F28T8	3	277	92	0.35	A	1.15	1.25	98	1.7	10.0	60.0 °F / NaN
F28T8	3	277	17	0.07	A	0.03	0.18	90	1.7	20.0	60.0 °F / NaN
F28T8	3	120	17	0.14	A	0.03	0.18	90	1.7	15.0	60.0 °F / NaN
F28T8	2	120	14	0.12	A	0.06	0.43	80	1.7	15.0	60.0 °F / NaN
F28T8	2	277	14	0.06	A	0.06	0.43	80	1.7	22.0	60.0 °F / NaN
F25T8/WM	2	120	56	0.48	A	1.25	2.23	99	1.7	10.0	60.0 °F / NaN
F25T8/WM	2	277	56	0.21	A	1.25	2.23	98	1.7	10.0	60.0 °F / NaN
F25T8/WM	3	120	76	0.66	A	1.15	1.51	99	1.7	10.0	60.0 °F / NaN
F25T8/WM	3	277	75	29.0	A	1.15	1.53	98	1.7	10.0	60.0 °F / NaN
F25T8/WM	3	120	17	0.14	A	0.10	0.59	98	1.7	15.0	60.0 °F / NaN
F25T8/WM	3	277	17	0.11	A	0.10	0.59	80	1.7	32.0	60.0 °F / NaN
F25T8/WM	2	120	14	0.12	A	0.13	0.93	98	1.7	15.0	60.0 °F / NaN
F25T8/WM	2	277	14	0.06	A	0.13	0.93	80	1.7	32.0	60.0 °F / NaN
F25T8	2	120	68	0.58	A	1.29	1.90	99	1.7	10.0	60.0 °F / NaN
F25T8	3	120	91	0.78	A	1.19	1.31	99	1.7	10.0	60.0 °F / NaN
F25T8	3	277	89	0.34	A	1.19	1.34	98	1.7	10.0	60.0 °F / NaN
F25T8	2	277	67	0.26	A	1.29	1.93	98	1.7	10.0	60.0 °F / NaN
F25T8	3	120	16	0.14	A	0.08	0.50	98	1.7	15.0	60.0 °F / NaN
F25T8	3	277	17	0.07	A	0.08	0.47	80	1.7	32.0	60.0 °F / NaN
F25T8	2	120	13	0.12	A	0.11	0.85	98	1.7	15.0	60.0 °F / NaN
F25T8	2	277	14	0.06	A	0.11	0.79	80	1.7	32.0	60.0 °F / NaN
F17T8/WM	2	120	41	0.36	A	1.21	2.95	99	1.7	10.0	60.0 °F / NaN
F17T8/WM	2	277	41	0.16	A	1.21	2.95	98	1.7	10.0	60.0 °F / NaN
F17T8/WM	3	120	55	0.47	A	1.11	2.02	99	1.7	10.0	60.0 °F / NaN

F17T8/WM	3	120	17	0.15 A	0.14	0.82	98	1.7	15.0	60.0 °F / NaN
F17T8/WM	3	277	18	0.07 A	0.14	0.78	80	1.7	32.0	60.0 °F / NaN
F17T8/WM	2	120	14	0.12 A	0.17	1.21	98	1.7	15.0	60.0 °F / NaN
F17T8/WM	2	277	15	0.07 A	0.17	1.13	80	1.7	32.0	60.0 °F / NaN
F17T8	2	120	48	0.41 A	1.25	2.60	99	1.7	10.0	60.0 °F / NaN
F17T8	2	277	48	0.18 A	1.25	2.60	98	1.7	10.0	60.0 °F / NaN
F17T8	3	120	65	0.56 A	1.15	1.77	99	1.7	10.0	60.0 °F / NaN
F17T8	3	277	64	0.24 A	1.15	1.80	98	1.7	10.0	60.0 °F / NaN
F17T8	3	120	17	0.15 A	0.12	0.71	98	1.7	15.0	60.0 °F / NaN
F17T8	3	277	18	0.08 A	0.12	0.67	80	1.7	32.0	60.0 °F / NaN
F17T8	2	120	15	0.13 A	0.15	1.00	98	1.7	15.0	60.0 °F / NaN
F17T8	2	277	15	0.07 A	0.15	1.00	80	1.7	32.0	60.0 °F / NaN

CAUTIONS & WARNINGS

NOTES

- Control wires open circuit operates at full power
- Control wires closed circuit operates at full dim
- The dimming range will be significantly shorter when using F17T8, F25T8 (3ft) or when delamping UltraMax® Dimming ballasts. Please see GELighting.com product specifications for a complete listing of product specifications by ballast, lamp type and number of lamps per ballast.

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.