

Presented By: iLightDepot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com

Customer Name:
Project Name:
Fixture Type:





GE
Lighting

78627 - GE432MAX-N/ULTRA

GE LFL UltraMax™ Electronic High Efficiency Multivolt Instant Start Ballast

- Energy saving high efficiency instant start electronic ballast (> 90%)
- Multi-Voltage Technology handles voltage from 120 to 277V
- UL Type CC Rating provides protection against arcing in electrical devices.
- Anti-Striation Control for better light quality, with no striations.
- UL 55C Ambient Rating - High Temperature Protection Circuit
- Cold temperature -20F Minimum Starting Temperature



GENERAL CHARACTERISTICS

Application	4 or 3- F32T8 120 to 277 "N".87 BF
Category	Linear Fluorescent
Ballast Type	Electronic - High Efficiency Multivolt Instant Start
Starting Method	Instant start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Ambient Temperature (MAX)	40.0 °C(4 °C)
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Additional Info	Anti-striation control/Auto-restart/Thermally protected

PRODUCT INFORMATION

Product Code	78627
Description	GE432MAX-N/ULTRA
Standard Package	Case
Standard Package GTIN	10043168786277
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168786270

DIMENSIONS

Case dimensions			
Length (L)	9.5 in(241.30 mm)		
Width (W)	1.3 in(33.02 mm)		
Height (H)	1.2 in(30.48 mm)		
Mounting dimensions			
Bracket Length (BL)	NaN in(NaN mm)		
Mount Length (M)	9.0 in(228.60 mm)		
Mount Width (X or F)	0.9 in(22.10 mm)		
Mount Slots (MS)	0.3 in(8.20 mm)		
Weight	1.1 lb		
Exit Type	Side		
Remote Mounting Distance	18.0 ft		
Remote Mounting Wire Gauge	18.0 AWG		
Lead lengths	Qty	Exit	Length (± 1 in.)
Black	1	Left	25.0 (635mm)
White	1	Left	25.0 (635mm)
Blue	2	Right	31.0 (787mm)
Red	2	Right	31.0 (787mm)
Yellow	2	Left	39.0 (991mm)

ELECTRICAL CHARACTERISTICS

Supply Current Frequency 50.0 Hz/60.0 Hz

SAFETY & PERFORMANCE

- cUL Listed
- FCC - CLASS A Non-Consumer
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type CC
- UL Type HL
- RoHs Compliant
- Meets ANSI Standard C82.11-Cons 2002
- Meets ANSI Standard C62.41-1991
- NEMA Premium®

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor	THD% (<=)	Min. Starting Temp (°F/°C)
FE15T8	3	120	41	0.34 A	0.85	2.07	99	1.4	10.0	0.0 °F / NaN
FE15T8	3	277	41	0.16 A	0.85	2.07	93	1.4	15.0	0.0 °F / NaN
FE15T8	4	120	48	0.41 A	0.77	1.60	99	1.4	10.0	0.0 °F / NaN
FE15T8	4	277	48	0.18 A	0.77	1.60	95	1.4	10.0	0.0 °F / NaN

F32T8/WM	3	120	84	0.71 A	0.91	1.08	99	1.4	10.0	50.0 °F / NaN
F32T8/WM	3	277	83	0.31 A	0.91	1.10	98	1.4	10.0	50.0 °F / NaN
F32T8/WM	4	120	102	0.85 A	0.87	0.85	99	1.4	10.0	50.0 °F / NaN
F32T8/WM	4	277	100	0.37 A	0.87	0.87	98	1.4	10.0	50.0 °F / NaN
F32T8/25W	3	120	71		0.89	1.25	99	1.4	10.0	50.0 °F / NaN
F32T8/25W	3	277	71		0.89	1.25	97	1.4	10.0	50.0 °F / NaN
F32T8/25W	4	120	87		0.87	1.00	99	1.4	10.0	50.0 °F / NaN
F32T8/25W	4	277	86		0.87	1.01	98	1.4	10.0	50.0 °F / NaN
F32T8	3	120	90	0.75 A	0.94	1.04	98	1.4	10.0	-22.0 °F / NaN
F32T8	3	277	88	0.32 A	0.94	1.07	98	1.4	10.0	-22.0 °F / NaN
F32T8	4	120	108	0.9 A	0.87	0.81	99	1.4	10.0	-22.0 °F / NaN
F32T8	4	277	106	0.39 A	0.87	0.82	98	1.4	10.0	-22.0 °F / NaN
F28T8	3	120	77	0.64 A	0.89	1.16	99	1.4	10.0	50.0 °F / NaN
F28T8	3	277	76	0.28 A	0.89	1.17	97	1.4	10.0	50.0 °F / NaN
F28T8	4	120	94	0.79 A	0.87	0.93	99	1.4	10.0	50.0 °F / NaN
F28T8	4	277	92	0.34 A	0.87	0.95	98	1.4	10.0	50.0 °F / NaN
F25T8	3	120	73	0.61 A	0.90	1.23	99	1.4	10.0	-22.0 °F / NaN
F25T8	4	120	87	0.73 A	0.82	0.94	99	1.4	10.0	-22.0 °F / NaN
F25T8	3	277	72	0.26 A	0.90	1.25	97	1.4	10.0	-22.0 °F / NaN
F25T8	4	277	85	0.31 A	0.82	0.96	98	1.4	10.0	-22.0 °F / NaN
F25T12	3	120	75	0.63 A	0.87	1.16	99	1.4	10.0	0.0 °F / NaN
F25T12	3	277	74	0.27 A	0.87	1.18	97	1.4	10.0	0.0 °F / NaN
F25T12	4	120	90	0.75 A	0.79	0.88	99	1.4	10.0	0.0 °F / NaN
F25T12	4	277	89	0.33 A	0.79	0.89	98	1.4	10.0	0.0 °F / NaN
F17T8	3	120	50	0.42 A	0.96	1.92	99	1.4	10.0	-22.0 °F / NaN
F17T8	3	277	50	0.19 A	0.96	1.92	95	1.4	10.0	-22.0 °F / NaN
F17T8	4	120	61	0.52 A	0.87	1.43	99	1.4	10.0	-22.0 °F / NaN
F17T8	4	277	60	0.23 A	0.87	1.45	96	1.4	10.0	-22.0 °F / NaN

CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Properly ground ballast and fixture.
 - Turn power off before servicing--see instructions.

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.