

Presented By: iLightDepot/GELightingDepot
Contact Phone: 513-272-0800
Contact E-mail: sales@ilightdepot.com

Customer Name:
Project Name:
Fixture Type:





GE
Lighting

71430 - GEC213-MVPS-3W

GE CFL Multi-Volt ProLine™ Electronic Program / Rapid Start Ballast

- Multi-Voltage technology means a single ballast handles voltage from 108V to 305V
- Programmed starting for extended lamp life
- End-of-Lamp-Life Protection
- Color Coded Poke-In Connectors simplifies wiring
- 3-Way Ballast Kit (-3W) includes mounting plate, lead wires, extraction tool and mounting hardware for side exit, bottom exit or bottom exit with studs mounting



GENERAL CHARACTERISTICS

Application	2 or 1- CFQ13W/G24q 120-277V Proline PS 3-Way Kit
Category	Compact Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Series
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Auto-restart/Thermally protected/Universal voltage

PRODUCT INFORMATION

Product Code	71430
Description	GEC213-MVPS-3W
Standard Package	Master
Standard Package GTIN	10043168714300
Standard Package Quantity	10
Sales Unit	Individual Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168714303

DIMENSIONS

Case dimensions	
Length (L)	5.0 in(127.00 mm)
Width (W)	2.4 in(60.96 mm)
Height (H)	1.0 in(25.40 mm)
Mounting dimensions	
Bracket Length (BL)	NaN in(NaN mm)
Mount Length (M)	4.6 in(117.60 mm)
Mount Width (X or F)	NaN in(NaN mm)
Mount Slots (MS)	NaN in(NaN mm)
Weight	0.57 lb
Exit Type	Poke-in
Remote Mounting Distance	20.0 ft
Remote Mounting Wire Gauge	18.0 AWG

ELECTRICAL CHARACTERISTICS

Supply Current Frequency	50.0 Hz/60.0 Hz
--------------------------	-----------------

SAFETY & PERFORMANCE

- CSA
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type CC
- UL Type HL
- FCC Part 18 Class B at 120 volts

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor	THD% (<=)	Min. Starting Temp (°F/°C)
CFTR18W/4P	1	120	20	0.17 A	1.00	5.00	99	1.5	12.0	-20.0 °F / NaN
CFTR18W/4P	1	277	20	0.07 A	1.00	5.00	97	1.5	12.0	-20.0 °F / NaN
CFTR13W/4P	1	120	16	0.16 A	1.00	6.25	96	1.5	10.0	-20.0 °F / NaN
CFTR13W/4P	1	277	16	0.06 A	1.00	6.25	96	1.5	10.0	-20.0 °F / NaN
CFTR13W/4P	2	120	29	0.25 A	1.00	3.45	99	1.5	10.0	-20.0 °F / NaN
CFTR13W/4P	2	277	29	0.11 A	1.00	3.45	99	1.5	10.0	-20.0 °F / NaN

CFS16W/4P	1	120	17	0.14 A	1.00	5.88	96	1.5	12.0	-20.0 °F / NaN
CFS16W/4P	1	277	17	0.06 A	1.00	5.88	96	1.5	12.0	-20.0 °F / NaN
CFS10W/4P	1	120	13	0.11 A	1.05	8.08	96	1.5	14.0	-20.0 °F / NaN
CFS10W/4P	1	277	13	0.05 A	1.05	8.08	96	1.5	14.0	-20.0 °F / NaN
CFS10W/4P	2	120	23	0.19 A	0.95	4.13	97	1.5	11.0	-20.0 °F / NaN
CFS10W/4P	2	277	23	0.09 A	0.95	4.13	97	1.5	11.0	-20.0 °F / NaN
CFQ18W/4P	1	120	20	0.17 A	1.00	5.00	99	1.5	12.0	-20.0 °F / NaN
CFQ18W/4P	1	277	20	0.07 A	1.00	5.00	97	1.5	12.0	-20.0 °F / NaN
CFQ13W/4P	1	120	16	0.16 A	1.00	6.25	96	1.5	10.0	-20.0 °F / NaN
CFQ13W/4P	1	277	16	0.06 A	1.00	6.25	96	1.5	10.0	-20.0 °F / NaN
CFQ13W/4P	2	120	29	0.25 A	1.00	3.45	99	1.5	10.0	-20.0 °F / NaN
CFQ13W/4P	2	277	29	0.11 A	1.00	3.45	99	1.5	10.0	-20.0 °F / NaN

CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Properly ground ballast and fixture.
 - Turn power off before servicing--see instructions.

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.