

**Presented By:** iLightDepot/GE Lighting Depot  
**Contact Phone:** 513-272-0800  
**Contact E-mail:** sales@ilightdepot.com

**Customer Name:**  
**Project Name:**  
**Fixture Type:**




**GE**  
**Lighting**

**72107 - GESB-2040-24-IP**

GE LFL Survivor™ Survivor Sign Ballast Magnetic T12 Sign Illuminating Ballast

- High output ballasts for rugged outdoor sign cabinet applications.
- Reliable low-temperature starting-as low as -20F.
- Ideal for high-moisture environments - UL type 2 outdoor and HL rating
- Class P thermal protection.



**GENERAL CHARACTERISTICS**

Application	2 to 4 lamp - 20 to 40ft, T12 Magnetic Sign Ballast
Category	Linear Fluorescent
Ballast Type	Magnetic - T12 Sign Illuminating
Starting Method	Rapid start
Lamp Wiring	Series
Line Voltage Regulation (+/-)	15.0 %
Ambient Temperature (MIN)	-20.0 °F
Ambient Temperature (MAX)	105.0 °F(41 °C)
Case Temperature (MAX)	90.0 °C
Ballast Factor	Normal
Enclosure Type	Metal Can
Additional Info	Thermally protected
Primary Application	Sign

**PRODUCT INFORMATION**

Product Code	72107
Description	GESB-2040-24-IP
Standard Package	Case
Standard Package GTIN	10043168721070
Standard Package Quantity	1
Sales Unit	Individual Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
UPC	043168721073

**DIMENSIONS**

<b>Case dimensions</b>			
Length (L)			19.5 in(495.30 mm)
Width (W)			3.2 in(81.03 mm)
Height (H)			2.4 in(61.72 mm)
<b>Mounting dimensions</b>			
Bracket Length (BL)			NaN in(NaN mm)
Mount Length (M)			18.6 in(472.95 mm)
Mount Width (X or F)			NaN in(NaN mm)
Mount Slots (MS)			NaN in(NaN mm)
Weight			22.2 lb
Lamp Footage Required (MIN)			20.0 ft
Lamp Footage Required (MAX)			40.0 ft
Exit Type			Side
Lead lengths	Qty	Exit	Length (± 1 in.)
White	1	Left	24 (610mm)
Black	1	Left	24 (610mm)
Yellow	2	Left	72 (1829mm)
Brown	2	Left	72 (1829mm)
Blue	2	Right	80 (2032mm)
Blue/White	2	Right	54 (1372mm)
Red	2	Right	80 (2032mm)

**ELECTRICAL CHARACTERISTICS**

Supply Current Frequency 60.0 Hz

**SAFETY & PERFORMANCE**

- UL type 2 Outdoor
- UL Listed
- UL Type HL

**SPECIFICATIONS BY LAMP & WATTAGE**

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)(<=)	Crest Factor	THD% (<=)	Min. Starting Temp (°F/°C)
F120T12/HO	2	120	255	3.0 A	0.75	0.29	71	1.8	30.0	-22.0 °F / NaN
F120T12/HO	3	120	357	3.4 A	0.82	0.23	89	1.7	15.0	-22.0 °F / NaN
F120T12/HO	4	120	464	4.0 A	0.85	0.18	97	1.7	12.0	-22.0 °F / NaN

**NOTES**

For additional information, visit [www.gelighting.com](http://www.gelighting.com)

- High Output 800mA RS Lamps
- System Watts refers to Maximum Watts

**WARRANTY INFORMATION**

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.