# Refit solutions from GE



# Type C **LED** Tubes – T5 Glass

#### **DESCRIPTION**

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

#### **FEATURES**

- T5 glass tube
- 1800-4500 lumen options available
- > 270 degree beam spread
- > 120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperature
- 50,000-hour rated life
- 5 year warranty
- UL and CUL-approved technologies
  - in compliance with UL 1598 certification

#### **BENEFITS**

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light –instant on
- Fully illuminates fixture 270° light distribution
- Easy disposal, non-hazardous waste

**ecomagination**™

To learn more about saving money and energy, go to: **gelighting.com/ThinkLED** 

When you Think LED lighting, Think GE.



## **Product Specifications**

	Base		Order			Case		Lumens	Initial Color		*Rated Life			#Location	Additional
Туре	Туре	Watts	Code	Description	Volts	Qty"	MOL (In)	Initial	Temp	CRI	L70 (Hrs)	DLC	UL	Rating	Information
Remote	LED Gla	ss T5 2ft	Tubes (O	perates on Remote Dri	ver)										
	G5	13	76150	LED15T5/G/2/830		20	22	1800	3000K	80+	50,000	-	Yes	Damp	Requires Driver
	G5	13	76164	LED15T5/G/2/835		20	22	1850	3500K	+08	50,000	-	Yes	Damp	Requires Driver
	G5	13	76129	LED15T5/G/2/840		20	22	1900	4000K	+08	50,000	-	Yes	Damp	Requires Driver
	G5	13	76167	LED15T5/G/2/850		20	22	1900	5000K	<b>80</b> +	50,000	-	Yes	Damp	Requires Driver
	G5	13	76192	LED15T5/G/2/865		20	22	1900	6500K	80+	50,000	-	Yes	Damp	Requires Driver

#### **Lightech Drivers - Non Dimming**

GE Product Code	Description	# of Lamps		
38970	LED15T8/DR/UN/2L	2		

#### **Lightech Drivers - Dimming**

GE Product Code	Description	# of Lamps
38975	LED15T8/DR/4DL	4
38974	LED15T8/DR/D2L	2
92013	LED36T/DR/4DL	4
63126	LED36T8/DR/D2L	2

#### **General Characteristics - Non Dimming**

GE Product Code	38970				
Output Current (A)	0.44*2				
Input Watt Range (W)	30				
Input Voltage (V)	120-277V				
Input Frequency (Hz)	50/60Hz				
Efficiency (%)	> .9%				
Output Type	DC				
Output Volt Range	27-33V				
Dimmability	None				
Ambient Temp Min	-4°F				
Ambient Temp Max	113°F				
Case Temperature	158°F				

#### **General Characteristics - Dimming**

	3				
GE Product Code	38974	63126	38975	92013	
Output Current (A)	0.44*2	1.06*2	0.44*4	1.06*4	
Input Watt Range (W)	30	72	60	144	
Input Voltage (V)	120-277V				
Input Frequency (Hz)	50/60Hz				
Efficiency (%)	>.9%				
Output Type	DC				
Output Volt Range					
Dimmability	0-10V				
Ambient Temp Min	-4°F				
Ambient Temp Max	113°F				
Case Temperature		15	8°F		

#### **Dimensions - Non Dimming**

GE Product Code	38970
Weight	1.01
Casing Length (in)	9.5
Casing Width (in)	1.3
Casing Height (in)	1.25
Lead Exit Length (in)	26
Input Wire Length (in)	36
Output Wire Length (in)	38

#### **Dimensions - Dimming**

		_			
	GE Product Code	38974	63126	38975	92013
	Weight	1.01	1.08	1.08	2.15
	Casing Length (in)	9.5	9.5	9.5	16.75
	Casing Width (in)	1.3	1.7	1.7	2.0
	Casing Height (in)	1.25	1.25	1.25	1.25
	Lead Exit Length (in)	26	26	26	26
	Input Wire Length (in)	36	36	36	36
	Output Wire Length (in)	42	42	42	42

# **ecomagination**<sup>™</sup>



Product is compliant with material restriction requirements of RoHS



### www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.