

# Refit Solutions from GE



Application illustration only, subject lamps not used in photo.

## Type C LED Tubes - High Lumen Glass

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED High Lumen Glass tubes are ideal for those seeking higher light levels while saving energy. Requires minimal installation time with a 5 year system warranty. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

### FEATURES

- 4' glass tube
- 2,700 -2,800 lumens
- > 133 total system lumens per watt (LPW)
- 3500K, 4000K and 5000K color temperature
- 50,000-hour rated life
- Open or enclosed fixtures
- 5 year warranty
- UL and cUL listed

### BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light
  - instant on
- No UV (Ultra Violet Rays)
- Fully illuminates fixture
  - >270 light distribution
- Easy disposal, non-hazardous waste

To learn more about saving money and energy, go to: [gelighting.com/ThinkLED](http://gelighting.com/ThinkLED)

When you Think LED lighting, Think GE.

ecomagination<sup>SM</sup>



imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

## Product Specifications

### Refit LED Tubes

GE Product Code	Description	Bulb Shape	Base	Watts	Case Quantity	Length (in)	Initial Lumens	Color Temp (K°)	CRI	*Rated Life L70 (Hrs)
62406	LED21T8/G4/835HL	T8	Med Bi-Pin (G13)	18	10	48"	2750	3500	80	50,000
62407	LED21T8/G4/840HL	T8	Med Bi-Pin (G13)	18	10	48"	2800	4000	80	50,000
62408	LED21T8/G4/850HL	T8	Med Bi-Pin (G13)	18	10	48"	2800	5000	80	50,000

### Lightech Drivers - Non Dimming

GE Product Code	Description	# of Lamps
94384	LED21T8/DR/1L	1
94385	LED21T8/DR/2L	2

### Lightech Drivers - Dimming

GE Product Code	Description	# of Lamps
60041	LED21T8/DR/D/2L	2
34016	LED21T8/DR/VLC/2L	2
62030	LED21T8/DR/D/4L	4

### General Characteristics - Non Dimming

GE Product Code	94384	94385
Output Current (A)	0.62	0.62*2
Input Watt (Max)	21	42
Input Voltage (V)	120-277V	
Input Frequency (Hz)	50/60Hz	
Efficiency (%)	> .9%	
Output Type	DC	
Output Volt Range	26-34V	
Dimmability	None	
Ambient Temp Min	-4°F	
Ambient Temp Max	113°F	
Case Temperature	158°F	

### General Characteristics - Dimming

GE Product Code	60041	34016	62030
Output Current (A)	0.62*2	0.62*2	0.62*4
Input Watt (Max)	42	42	84
Input Voltage (V)	120-277V		
Input Frequency (Hz)	50/60Hz		
Efficiency (%)	> .9%		
Output Type	DC		
Output Volt Range	26-34V		
Dimmability	0-10V		
Ambient Temp Min	-4°F		
Ambient Temp Max	113°F		
Case Temperature	158°F		

### Dimensions - Non Dimming

GE Product Code	94384	94385
Weight	1.01	1.01
Casing Length (in)	9.5	
Casing Width (in)	1.3	
Casing Height (in)	1	
Lead Exit Length (in)	26	
Input Wire Length (in)	36	
Output Wire Length (in)	38	

### Dimensions - Dimming

GE Product Code	34016	60041	62030
Weight	1.01	1.08	
Casing Length (in)	9.5		
Casing Width (in)	1.7		
Casing Height (in)	1		
Lead Exit Length (in)	26		
Input Wire Length (in)	36		
Output Wire Length (in)	42		

ecomagination<sup>SM</sup>



Product is compliant with material restriction requirements of RoHS



[www.gelighting.com](http://www.gelighting.com)

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

LEDL018 (Rev 10/27/16)