

# Refit Solutions from GE



Application illustration only, subject lamps not used in photo.

## Type C LED Tubes - assembled in USA

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

### FEATURES

- 4' and 8' glass tubes
- 2600-4400 lumen options available
- >120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K and 5000K color temperatures
- 50,000-hour rated life
- UL and CUL listed
  - in compliance with UL 1598 certification
- Open or Enclosed Fixtures
- Damp rating
- 5 year warranty

### BENEFITS

- Fast and easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light – instant on
- Fully illuminates fixture
  - 270° light distribution
- Easy disposal, non-hazardous waste
- State-of-Art USA Assembly
  - Perfect for special projects

To learn more about saving money and energy, go to: [gelighting.com/ThinkLED](http://gelighting.com/ThinkLED)

When you Think LED lighting, Think GE.

ecomagination<sup>SM</sup>



imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

## Product Specifications

### Refit LED Tubes

GE Product Code	Description	Bulb Shape	Base	Tube Watts	Case Quantity	Length (In)	Initial Lumens	Color Temp (K°)	CRI	*Rated Life L70 (Hrs)
<b>4ft LED Tubes</b>										
91475	LED21T8/G4/830US	T8	Medium Bi-Pin (G13)	18	20	48"	2600	3000	+80	50,000
91496	LED21T8/G4/835US	T8	Medium Bi-Pin (G13)	18	20	48"	2600	3500	+80	50,000
91497	LED21T8/G4/840US	T8	Medium Bi-Pin (G13)	18	20	48"	2600	4000	+80	50,000
91498	LED21T8/G4/850US	T8	Medium Bi-Pin (G13)	18	20	48"	2600	5000	+80	50,000
<b>8ft LED Tubes</b>										
62326	LED36T8/G/8/830	T8	Single Pin (Fa8)	30	20	96"	4200	3000	+80	50,000
62327	LED36T8/G/8/835	T8	Single Pin (Fa8)	30	20	96"	4400	3500	+80	50,000
62329	LED36T8/G/8/840	T8	Single Pin (Fa8)	30	20	96"	4400	4000	+80	50,000
62349	LED36T8/G/8/850	T8	Single Pin (Fa8)	30	20	96"	4400	5000	+80	50,000

### Lightech Drivers - Non Dimming

GE Product Code	Description	# of Lamps
94384	LED21T8/DR/1L	1
94385	LED21T8/DR/2L	2

### Lightech Drivers - Dimming

GE Product Code	Description	# of Lamps
60041	LED21T8/DR/D/2L	2
34016	LED21T8/DR/VLC/2L	2
62030	LED21T8/DR/D/4L	4
63126	LED36T8/DR/D2L	2

### General Characteristics - Non Dimming

GE Product Code	94384	94385
Output Current (A)	0.62	0.62*2
Input Watt (Max)	21	42
Input Voltage (V)	120-277V	
Input Frequency (Hz)	50/60Hz	
Efficiency (%)	> .9%	
Output Type	DC	
Output Volt Range	27-33V	
Dimmability	None	
Ambient Temp Min	-4°F	
Ambient Temp Max	104°F	
Case Temperature	158°F	

### General Characteristics - Dimming

GE Product Code	60041	34016	62030	63126
Output Current (A)	0.62*2	0.62*2	0.62*4	0.54*2
Input Watt (Max)	42	42	84	72 (36 x 2)
Input Voltage (V)	120-277V			
Input Frequency (Hz)	50/60Hz			
Efficiency (%)	> .9%			
Output Type	DC			
Output Volt Range	27-33V		26-34V	
Dimmability	0-10V		0-10V	
Ambient Temp Min	-4°F		-4°F	
Ambient Temp Max	104°F		113°F	
Case Temperature	158°F		158°F	

### Dimensions - Non Dimming

GE Product Code	94384	94385
Weight	1.01	1.08
Casing Length (in)	9.5	
Casing Width (in)	1.3	
Casing Height (in)	1	
Lead Exit Length (in)	26	
Input Wire Length (in)	36	
Output Wire Length (in)	38	

### Dimensions - Dimming

GE Product Code	60041	34016	62030	63126
Weight	1.01	1.08	1.08	1.01
Casing Length (in)	9.5	9.5	9.5	9.5
Casing Width (in)	1.3	1.7	1.3	1.3
Casing Height (in)	1	1	1	1
Lead Exit Length (in)	26	26	26	26
Input Wire Length (in)	36	36	36	36
Output Wire Length (in)	38	42	42	38

ecomagination<sup>SM</sup>



Product is compliant with material restriction requirements of RoHS



[www.gelighting.com](http://www.gelighting.com)

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

LEDL035 (Rev 12/07/16)