

# Refit solutions from GE



Application illustration only, subject lamps not used in photo.

## Type A Integrated LED Tubes – T5 Glass

### DESCRIPTION

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by an internal GE Lightech™ driver. GE integrated LED tubes run on electronic instant-start or programmed start ballasts.

### FEATURES

- T5 glass tube
- 3650-3900 lumen options available
- > 120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperature
- 50,000-hour rated life
- 5 year warranty
- UL and CUL-approved technologies
  - in compliance with UL 1598 certification

### BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- Low installation cost
- No rewiring required
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light – instant on
- Fully illuminates fixture
  - >270° light distribution
- Easy disposal, non-hazardous waste

To learn more about saving money and energy, go to: <http://products.currentbyge.com>.

ecomagination<sup>SM</sup>

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

**current**  
powered by GE



## Product Specifications

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	*Rated Life L70 (Hrs)	DLC	UL	#Location Rating	Additional Information
Integrated LED Glass T5 4ft Tubes (Operates on Instant Start or Program Start Ballast)															
G5	25.5	19203	LED26ET5/G/4/830			20	46	3650	3000K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast
G5	25.5	19221	LED26ET5/G/4/835			20	46	3750	3500K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast
G5	25.5	19227	LED26ET5/G/4/840			20	46	3800	4000K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast
G5	25.5	19348	LED26ET5/G/4/850			20	46	3900	5000K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast
G5	25.5	19488	LED26ET5/G/4/865			20	46	3800	6500K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast

ecomagination<sup>SM</sup>



Product is compliant with material restriction requirements of RoHS

**current**  
powered by GE

<http://products.currentbyge.com>

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2017 GE.

LEDL045 (Rev 09/06/17)

