

11345 - GE Lucalox® High Pressure Sodium B17 LU50/MED/ECO

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Medium Screw

Open or enclosed fixtures

High Intensity Discharge

Screw-In

158.6

Clear 13.7

E26

ED17

24000 h

Soft glass

Base Description		
Base Type		
Lamp Enclosure Type (LET)		
Mercury-Picogrm per mean Im hr		
Rated Life Hours-nominal		
Bulb Finishes and Colors		
Mercury Content EMEA ONLY		
Bulb Material		
Product Technology		
Base		
Bulb Shape		

PHOTOMETRIC CHARACTERISTICS

Effective Arc Length	0.8 in
Mean Lumens nominal	3600 lm
Nominal Lumens per Watt	80 Im
Color Rendering Index-CRI	22
PRODUCT INFORMATION	
Product Code	11345
Description	LU50/MED/ECO
Alternative Unit Of Measure	CASE
Standard Package Quantity	6
Ean UPC	043168113458
Standard Package GTIN	10043168113455
No Of Items Per Sales Unit	
No Of Items Per Standard Package	6
Sales Unit	Case
UCC	043168113458
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168113458
Standard Package GTIN	00043168113458
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	
DIMENSIONS	
Diameter	2.12 in
Light Center Length Millimeter	3.43 in
Nominal Length	5.43 in
ELECTRICAL CHARACTERISTICS	
Burn Position Open Circuit Voltage (BMS lag ballast)	Universal burning pos
UDEN GICUN VONAGE (BIVIS 180 DAMAST)	110 V

Bur

Burn Position	Universal burning position
Open Circuit Voltage (RMS lag ballast) (MIN)	110 V
Rated power (Watts)	50 W

CAUTIONS & WARNINGS

WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: http://www.fda.gov/cdrh/radhealth/products/urburns.html

Caution

Lamp may shatter and cause injury if broken

- Dispose of lamp in a closed container.
- Do not use excessive force when installing lamp.

Do not use lamp if outer glass is scratched or broken.

Wear safety glasses and gloves when handling lamp.

Risk of Burn

Allow lamp to cool before handling.

Do not turn on lamp until fully installed.

Warning

Contains sodium ? chemical burn risk

Avoid skin contact with broken pieces.

Risk of Electric Shock

Do not use where directly exposed to water or outdoors without an enclosed fixture.

Turn power off before inspection

installation or removal.

Risk of Fire

Keep combustible materials away from lamp.

Use in fixture rated for this product.

Unexpected lamp rupture may cause injury, fire, or property damage


Do not exceed rated voltage.


Do not store flammable materials near/below S-rated lamp in open fixture

Do not turn on lamp until fully installed.

Do not use lamp if outer glass is scratched or broken.

Do not use where directly exposed to water or outdoors





Mar 8, 2021 8:16:54 PM | For additional information, visit https://products.gecurrent.com/



Lamp Contains Mercury Manage in Accord with Disposal Laws See : www.lamprecycle.org or 1-800-327-0097