

Description

The H7 recessed housing is the standard in the industry for both light commercial and residential applications. H7 series features full-frame design, robust construction, feed-through listing, Got Nail! bar hangers; and may support use of higher wattage lamps. A wide variety of trims allows a number of different lighting effects to be created with one basic housing. H7ICAT is for installations where the housing will be in direct contact with insulation,* and its Air-Tite design will also meet restricted air flow code requirements. May be retrofit with compatible Halo LED lighting systems.

Catalog #	Туре
Project	
Comments	Date
Prepared by	

Specification Features

Housing

- · Single wall aluminum housing
- Aluminum construction for greater heat dissipation
- Sealed and gasketed for Air-Tite™ ready installation
- Designed for insulated ceilings in direct contact with insulation* (May also be installed in non-insulated ceilings)

Socket Plate

- Rigid socket plate adjusts and locks without tools for various lamp sizes
- Socket plate and bracket may be removed when using socket supporting trims

Plaster Frame

- Housing adjusts in plaster frame to accommodate up to 1" ceiling thickness
- · Galvanized steel construction
- · Plaster frame features include:
- Regressed locking screw for securing hanger bars
- Cutouts for easily crimping hanger bars in position
- · Halo name embossed on plaster
- The housing may be removed from plaster frame to provide access to the junction box
- Pre-installed Air-Tite ready ceiling contact gasket

Got Nail!™ Bar Hanger Bracket

Bar Hanger Features include:

- Pre-installed nail easily installs lumber and laminated beams
- Safety and guidance system prevents snagging, ensures smooth straight nail penetration and allows bar hangers to be easily removed if necessary
- Automatic leveling flange aligns the housing and lets you hold the housing in place with one hand while driving nails

- · Five additional mounting points
- Mounting point on top for hanger wire connection
- Integral T-bar clips snaps onto T-bars no additional clips required

q-Channel bars with Pass-N-Thru™

- · q-Channel bars feature an unique inverted "q" interlocking channel for rigidity and stability
- Pass-N-Thru™ feature allows bars to cross-over for tool-less shortening in tight spaces less than 12" without removing from the plaster frame. Push bars together and flex at score hole break points
- · Housing can be positioned at any point within 24" joist span
- Bar hangers may be repositioned 90° on the frame

Slide-N-Side™ Junction Box

Junction box features include:

- Slide-N-Side™ connectors allow non-metallic sheathed cable for both U.S. and Canada to be installed without tools and without removing knockouts
 - Allows wiring connections to be made outside the junction box
 - Simply insert the cable directly into the trap after connections are
 - accommodates the following standard non-metallic sheathed cable types: (US) #14/2 , #14/3, #12/2, #12/3 (Canada) #14/2, #14/3, #12/2
- installs in regular lumber, engineered Positioned to accommodate straight conduit runs
 - Seven 1/2" trade size conduit knockouts with true pry-out slots
 - · cULus Listed 26 in 3 box volume
 - Listed for through branch (8) No. 12 AWG branch circuit 90° C conductors through the box

Quick Connect™

· Three 4-port push-in "Quick

- Connect" wire nuts included in junction box
- Speed installation and increase reliability
- No additional wire nuts required
- · Simply strip and insert supply wires

Socket

- Porcelain socket with nickel plated brass screw shell
- Snap-in springs secure socket to socket plate, and may be detached when using socket supporting trims
- Overspray protector included

Thermal Protector

Self resetting thermal protector deactivates fixture if overheating occurs due to improper lamping or misapplied insulation

Trims

Halo Fit-All concept offers multiple trim options in a variety of design styles, and functional beam distributions to control beam angle and lumen delivery in accommodating various lamp types including Halogen, CFL and LED

Compliance

- cULus Listed 1598 Luminaire
- · cULus Listed Damp Location
- cULus Listed for Wet Location, covered ceiling, with select trims
- cULus Listed for direct contact with insulation and combustible material*
- · cULus Listed for feed through
- · Air-Tite code compliant. Certified under ASTM E283; not exceeding 2.0 cfm (0.944 L/s) air leakage rate tested at a 1.57 psf (75 Pa) pressure differential
- · RoHS compliant
- *Not to be used in direct contact with spray foam insulation (Consult NEMA LSD57-2013)








H7ICAT


6" IC, New Construction, 120V

FOR USE IN INSULATED **CEILINGS**

FOR DIRECT CONTACT WITH INSULATION*

Dimensions





Special Features

Got-Nail!™ bar hangers q-Channel bars with Pass-N-Thru™ Slide-N-Side™ junction box Quick Connect™ push wire nuts Air-Tite™ code compliant



Ordering Information

Sample Number: H7ICAT 6110WB

Order housing, trim and lamp (by others) separately for a complete luminaire.

H7ICAT = 6" IC, Air-tite, New Construction, 120V

Trims

Reflectors



30 Reflector, Self-flange

OD: 7-1/4" [184mm]
30HAT=Haze Reflector, White Trim 30RGAT=Residential Gold Reflector, White Trim 30CAT=Clear Specular Reflector, White Trim



30SBAT Reflector, Self-flange

OD: 7-1/4" [184mm]

30SBAT=Black Specular Reflector, Self-flange



404 Specular Reflector

OD: 7-1/4" [184mm]

404C=Clear Specular Reflector, White Trim 404H=Haze Reflector, White Trim 404SN=Satin Nickel Reflector and Trim 404TBZ=Tuscan Bronze Reflector and Trim



426 Reflector Cone OD: 7-1/4" [184mm]

426=Clear Specular Reflector Cone, White Trim 426MB=Black Specular Reflector Cone, White Trim

426H=Haze Reflector Cone, White Trim 426SN=Satin Nickel Reflector Cone and Trim 426TBZ=Tuscan Bronze Reflector Cone and Trim



429 Dayform White Cone OD: 7-1/4" [184mm]

429P=White Reflector and Trim



4041 White Reflector, Self-flange

OD: 7-1/4" [184mm] 4041P=White Reflector and Trim



4261 White Reflector Cone, Self-flange OD: 7-1/4" [184mm]

4261P=White Reflector and Trim



6106 Straight Reflector Cone, Self-flange

OD: 7-3/4" [197mm] 6106SC=Specular Reflector, White Trim



6107 Tapered Reflector, Self-flange

OD: 7-3/4" [197mm] 6107SC=Specular Reflector, White Trim



6120 Full Cone Reflector, Self-flange OD: 7-3/4" [197mm]

6120WH=White Reflector and Trim 6120SN=Satin Nickel Reflector and Trim 6120TBZ=Tuscan Bronze Reflector and Trim



6121 Shallow Full Cone Reflector, Self-flange

OD: 7-3/4" [197mm]

6121WH=White Reflector and Trim





30 Baffle, Self-flange OD: 7-1/4" [184mm]

30WAT=White Baffle, Reflector and Trim 30WATH=White Baffle, Clear Reflector and White Trim

30PAT=Black Baffle, Clear Reflector and White Trim

30SNAT=Satin Nickel Baffle, Reflector and Trim 30TBZAT=Tuscan Bronze Baffle, Reflector and



310 Coilex® Baffle OD: 7-1/4" [184mm] 310W=White Coilex Baffle and Trim 310P=Black Coilex Baffle, White Trim 310SN=Black Coilex Baffle, Satin Nickel Trim

310TBZ=Black Coilex Baffle, Tuscan Bronze Trim



312 Coilex® Baffle OD: 7-1/4" [184mm]

312W=White Coilex Baffle and Trim 312P=Black Coilex Baffle, White Trim



353 Metal Baffle OD: 7-1/4" [184mm]

353SN=Satin Nickel Baffle and Trim 353TBZ=Tuscan Bronze Baffle and Trim



6100 Tapered Metal Baffle with (2) Trim Rings OD: 7-1/8" [181mm]

6100WB=White Baffle, Narrow and Wide White Trims (included)

6100BB=Black Baffle, Narrow and Wide White Trims (included)



6101 Straight Metal Baffle with (2) Trim Rings OD: 7-1/8" [181mm]

6101WB=White Baffle, Narrow and Wide White Trims (included)

6101BB=Black Baffle, Narrow and Wide White Trims (included)



6102 Tapered Metal Baffle, Self-flange

OD: 7-3/4" [197mm]

6102WB=White Baffle and Trim 6102BB=Black Baffle, White Trim



6103 Straight Metal Baffle, Self-flange

OD: 7-3/4" [197mm] 6103WB=White Baffle and Trim 6103BB=Black Baffle, White Trim



6108 Coilex[®] Straight Plastic Baffle, Self-flange OD: 7-3/4" [197mm] 6108WB=White Plastic Straight Coilex Baffle,

White Trim 6108BB=Black Plastic Straight Coilex Baffle,

White Trim

6108BKBB=Black Plastic Straight Coilex Baffle, Black Trim



6109 Coilex® Tapered Baffle, Self-flange OD: 7-3/4" [197mm]

6109WB=White Tapered Coilex Baffle,

White Trim 6109BB=Black Tapered Coilex Baffle,

White Trim 6109BKBB=Black Tapered Coilex Baffle, Black Trim



6110 Perftex Baffle, Self-flange OD: 7-3/4" [197mm] 6110WB=White Perftex Baffle and Trim 6110BB=Black Perftex Baffle, White Trim 6110BKBB=Black Perftex Baffle and Trim



<u>6125 Full Cone Baffle, Self-flange</u>

OD: 7-3/4" [197mm] 6125WB=White Baffle and Trim 6125BB=Black Baffle, White Trim 6125BKBB=Black Baffle and Trim



6126 Shallow Full Cone Baffle, Self-flange

OD: 7-3/4" [197mm] 6126WB=White Baffle and Trim 6126BB=Black Baffle, White Trim





74 PAR30 Eyeball 30° Tilt, Self-flange OD: 8" [203mm] 74P=White Eyeball and Trim



76 PAR38 Gimbal 30° Tilt, Self-flange

OD: 8" [203mm] 76P=White Gimbal and Trim



78 BR/PAR30 Eyeball 30° Tilt, Self-flange

OD: 8" [203mm]

78P=White Eyeball and Trim 78PAT=White Eyeball and Trim, Air-Tite 78SN=Satin Nickel Eyeball and Trim 78TBZ=Tuscan Bronze Eyeball and Trim



376 PAR30 Regressed Gimbal 30° Tilt,

Self-flange OD: 7-1/4" [184mm] 376W=White Baffle and Trim 376P=Black Baffle and White Trim



378 PAR30 Regressed Gimbal with Splay 25° Tilt,

Self-flange OD: 7-1/4" [184mm]

378P=White Splay and Trim 378=Clear Specular Splay and White Trim



Self-flange
OD: 7-1/4" [184mm]
420W=White Eyeball, Baffle and Trim 420P=White Eyeball, Black Baffle, White Trim



478 PAR38 Adjustable Regressed Gimbal with

Splay 25° Tilt, Self-flange OD: 7-1/4" [184mm] 478P=White Splay and Trim





OD: 7-3/4" [197mm] 6170WH=White Gimbal and Trim 6170BK=Black Gimbal and Trim 6170SN=Satin Nickel Gimbal and Trim 6170TBZ=Tuscan Bronze Gimbal and Trim



6215 PAR30 Double Gimbal 35°-50° Tilt,

Self-flange OD: 7-3/4" [197mm]

6215WH=White Gimbal and Trim 6215BK=Black Gimbal and Trim 6215SN=Satin Nickel Gimbal and Trim



6215TBZ=Tuscan Bronze Gimbal and Trim 6222 Regressed PAR30 Adjustable 45° Tilt,

Self-flange OD: 7-3/4" [197mm] 6222WB=White Baffle and Trim

6222BB=Black Baffle and Trim 6222SC=Specular Clear Reflector, White Trim 6222H=Haze Reflector, White Trim


Lenses & Wet Location Showerlights

170 Albalite Lens with Reflector OD: 8" [203mm] 170P=Frosted Albalite Glass Lens, White Trim



OD: 8" [203mm] 171P=Drop Opal Glass Lens, White Trim 171PS=Drop Opal Glass Lens, White Plastic Trim, Showerlight, Air-Tite

170PS=Frosted Albalite Glass Lens, White



172 Dome Lens with Reflector
OD: 7-3/4" [197mm]
172PS=Frosted Glass Dome, White Plastic Trim 172SNS=Frosted Glass Dome, Satin Nickel Plastic Trim

172TBZS=Frosted Glass Dome, Tuscan Bronze Plastic Trim

*Outdoor rated lamp only (purchase separately)

continued



Ordering Information

Sample Number: H7ICAT 6110WB

Order housing, trim and lamp (by others) separately for a complete luminaire.

H7ICAT = 6" IC, Air-tite, New Construction, 120V

Trims

Lenses & Wet Location Showerlights



173 Fresnel Lens with Reflector

OD: 8" [203mm]

173P=Fresnel Glass Lens, White Trim 173PS=Fresnel Glass Lens, White Plastic Trim, Showerlight, Air-Tite



6145 Open Wet Location, Shallow Reflector,

Self-flange - Showerlight* OD: 7-3/4" [197mm]

6145WH=White Reflector and Trim 6145SN=Satin Nickel Reflector and Trim 6145TBZ=Tuscan Bronze Reflector and Trim



6146 Open Wet Location, Full Reflector, Self-flange - Showerlight* OD: 7-3/4" [197mm]

6146WH=White Reflector and Trim 6146SN=Satin Nickel Reflector and Trim 6146TBZ=Tuscan Bronze Reflector and Trim



6150 Frost Dome Glass Lens, Self-flange

OD: 7-3/4" [197mm]

6150WH=Frost Dome Glass Lens with Reflector, White Plastic Trim

6150SN=Frost Dome Glass Lens with Reflector, Satin Nickel Plastic Trim

6150TBZ=Frost Dome Glass Lens with Reflector, Tuscan Bronze Plastic Trim



6162 Drop Opal Plastic Lens, Self-flange -

Showerlight
OD: 7-3/4" [197mm]

6162WH=Drop Opal Plastic Lens with Reflector,

White Plastic Trim



6230 Squircle Frost Glass Lens,

Metal Trim - Showerlight
OD: 7-1/4" [183mm]
6230AH=Frost Glass Lens, Aluminum Haze

Squircle Trim

6230PN=Frost Glass Lens, Polished Nickel

Squircle Trim

6230SN=Frost Glass Lens, Satin Nickel

Squircle Trim

6230TBZ=Frost Glass Lens, Tuscan Bronze Squircle Trim



6255 Soft Square, Frost Curve Glass Lens,

Self-flange - Showerlight
OD: 7-1/4" [183mm]
6255WH=Frost Curve Glass Lens with Reflector,

White Plastic Trim

6255SN=Frost Curve Glass Lens with Reflector,

Satin Nickel Plastic Trim

6255TBZ=Frost Curve Glass Lens with Reflector, Tuscan Bronze Plastic Trim

Open, Splay & Wall Wash

300 Open Trim with Fixed Socket Bracket,

Self-flange OD: 7-1/4" [183mm]

300P=Self-flange with White Open Trim 300SN=Self-flange with Satin Nickel Open Trim 300TBZ=Self-flange with Tuscan Bronze Open Trim

327 White Splay Trim with Fixed Socket

Bracket, Self-flange OD: 7-3/4" [197mm]

327P=White Splay Trim with Socket Bracket



328 White Splay Trim 0D: 7-3/4" [197mm]

328P=White Splay Trim



430 Wall Wash with Baffle & Full Reflector

OD: 7-1/4" [183mm] 430W=White Baffle, with Upper Reflector, White Trim

430P=Black Baffle, with Upper Reflector, White Trim

Accessories

Designer Finish Trim Rings

TRM6C=Chrome

TRM6SN=Satin Nickel

TRM6TBZ=Tuscan Bronze

TRM6MB=Black Metal TRM7MB=Black plastic Metal 7 1/4" OD. Compatible with 310*, 312*, 376, 378, 400, 404, 405, 410, 416, 419, 420, 424, 425, 426*, 429*, 455CG, 455SC, 456P, 456W, 477, 478, 1412, 1416, 1475.

Oversized Trim Rings OT400P=6" ID x 9-1/4" OD, Oversized white metal trim ring for designated 6" trims.

OT403P=6" ID x 8" OD, Oversized gloos white plastic trim ring for designated 6" trims.

H930 R/PAR Lamp Aiming Accessory H930=For H7T, H7RT, H7ICT, H7ICAT, H7RICT, H7RICAT housings with 310 and 426 trims. Allows lamp to be aimed up to 30° from vertical and rotated 358°. See housing-trim selection for lamp

*Originally supplied with TRM6P white metal trim rings. All others are suppled with white plastic

*Outdoor rated lamp only (purchase separately)

See www.eaton.com/lighting/legal.