



LED BACKLIT PANEL



PRODUCT FEATURES

- Tunable Wattage & CCT Models Available
- Seamless White Finish Frame
- Concave-Convex Edge Fold Aluminum Backplate
- Back-lit LED Technology
- PMMA Optic Anti-Yellow
- DLC Listed
- UL Listed
- 0-10V Dimming
- High Luminous Efficiency
- Glare-free Lighting
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operational Temperature Range -4°F to 104°F (-20°C to 40°C)

PRODUCT SPECIFICATIONS

| MODEL | POWER (W) | LUMENS (LM) | CCT (K) | DIMENSIONS (FT) | EFFICIENCY (lm/W) | BEAM ANGLE |
|---|-----------|-------------|-------------|-----------------|-------------------|------------|
| CLP99-2X2BLP-29W40K / 50K | 29 | 3190 | 4000 / 5000 | 2 X 2 | 110 | 120° |
| CLP99-2X4BLP-49W40K / 50K | 49 | 5300 | 4000 / 5000 | 2 X 4 | 108 | 120° |
| CLP99-2X2BLP-15/19/24/29W-30K-40K-50K TUNABLE WATTAGE & CCT | 15 | 1950 | 3000 | 2 X 2 | 130 | 120° |
| | 19 | 2470 | 4000 | | | |
| | 24 | 3120 | 5000 | | | |
| | 29 | 3770 | 5000 | | | |
| CLP99-2X4BLP-29/34/39/49W-30K-40K-50K TUNABLE WATTAGE & CCT | 29 | 3770 | 3000 | 2 X 4 | 130 | 120° |
| | 34 | 4420 | 4000 | | | |
| | 39 | 5070 | 5000 | | | |
| | 49 | 6370 | 5000 | | | |

