



LED DUAL MODE TUBES



PRODUCT FEATURES

- Direct Replacement / Plug & Play Mode (Type A) *
- Retrofit / Bypass Mode - Double and Single Ended (Type B)
- Bypass installation utilizes existing lamp holders
- Film Coated Shatter Resistant Glass Tube
- Frosted & Clear Applications Available
- Instant On / No Flicker
- Non-Dimming
- IP20 Rated
- 120-277 Voltage Rating, PF > 0.9
- 80+ CRI
- G13 Mounting
- Aluminum End Caps
- DLC Listed
- UL Classified & UL Listed
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operating Temperature: -4°F to 113°F (-20°C to 45°C)

* See Ballast Compatibility Chart

PRODUCT SPECIFICATIONS

MODEL	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	DIFFUSER	BEAM ANGLE
CLT94-18WT8AM-40-AB	18	2300	4000	48.0	Frosted	220°
CLT94-18WT8AM-50-AB	18	2300	5000	48.0	Frosted	220°
CLT94-18WT8AT-50-AB	18	2300	5000	48.0	Transparent	220°

