



# KT-EMRG-650-CFL2

## EMERGENCY BALLAST



### PRODUCT FEATURES

<b>INPUT VOLTS:</b> 120/277V, 60Hz	<b>LIGHT OUTPUT:</b> 650 Lumen	<b>BATTERY:</b> 3.6V Sealed NiCD
	<b>ILLUMINATION TIME:</b> 90 Minutes	<b>WARRANTY:</b> 5 Years

### OPERATING DETAILS

- For use in new or existing fixtures, with or without an AC ballast, where emergency lighting is needed.
- Operates one lamp in the emergency mode.
- 2-in-1 LED indicator light and push-to-test switch (for mandated code compliance testing).
- Internal battery automatically connects to the fluorescent lamp for minimum 90 minute emergency illumination via an internal solid-state transfer switch.
- A discharged battery completely recharges in 24 hours, via a fully automatic solid-state, two-rate charger.


### LAMP COMPATIBILITY

- Compatible with most one-, two-, three-, and four-lamp electronic, standard and dimming AC ballasts.
- Operates the following lamps under emergency power:

	2-Pin CFL (W)
<b>No. of Lamps</b>	1
<b>Wattage</b>	13-26

### PHYSICAL SPECIFICATIONS

#### CASE DIMENSIONS



<b>LENGTH</b>	9.50"
<b>WIDTH</b>	2.40"
<b>HEIGHT</b>	1.50"
<b>CASE MATERIAL:</b>	Painted Steel (White Finish)
<b>ADDITIONAL FEATURES:</b>	2' Flex Conduit on Both Ends of Ballast

#### INITIAL LUMEN OUTPUT

LAMP	INITIAL LUMENS
	1-Lamp
2-Pin PL CF 13W	380
2-Pin PL CF 18W	550
2-Pin PL CF 26W	650



# KT-EMRG-650-CFL2

## EMERGENCY BALLAST

### MOUNTING

- UL listed for factory or field installation. Suitable for damp location.
- Can be mounted inside, on top, or remote from the fixture.\*
- Designed to be used in both switched and unswitched fixtures.


*\* When battery packs are remote mounted, the remote distance cannot exceed 1/2 of the distance from ballast to lamp specified by the AC ballast manufacturer. The maximum allowable remote mounting distance is 50 feet.*

### ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KT-EMRG-650-CFL2-DP	Distributor Pack	1	Quick Ship

### CATALOG NUMBER BREAKDOWN

# KT-EMRG-650-CFL2-DP



Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State codes.

Keystone Technologies • 208 Progress Drive, Montgomeryville, PA 18936 • Phone (800) 464-2680 • Fax (888) 966-0556 • [www.keystoneballast.com](http://www.keystoneballast.com)